

**DIGITAL BROADCAST PROGRAM ORDERING**

**Related Applications**

This application is a continuation-in-part of application Serial Number 08/711,742, filed September 10, 1996, entitled TELEVISION PROGRAM DELIVERY SYSTEM, which is a continuation of application Serial Number 08/160,191, filed December 2, 1993, entitled TELEVISION PROGRAM DELIVERY SYSTEM, now U.S. Patent No. 5, 559,549.

*WP*  
*2/21*  
This application is also a continuation of application Serial Number 08/735,552, filed October 23, 1996, entitled NETWORK CONTROLLER FOR CABLE TELEVISION DELIVERY SYSTEMS, which is a continuation of application Serial Number 08/160,280, filed December 2, 1993, entitled NETWORK CONTROLLER FOR CABLE TELEVISION DELIVERY SYSTEMS, now U.S. Patent No. 5,600,364, which is a continuation-in-part of application Serial Number 07/991,074 filed December 9, 1992 entitled TELEVISION PROGRAM PACKAGING AND DELIVERY SYSTEM WITH MENU DRIVEN SUBSCRIBER ACCESS.

This application is also a continuation of application Serial Number 08/352,205 filed December 2, 1994, entitled NETWORK MANAGER FOR CABLE TELEVISION SYSTEM HEADENDS, which is a continuation-in-part of application Serial Number 07/991,074, filed December 9, 1992, entitled TELEVISION PROGRAM PACKAGING AND DELIVERY SYSTEM WITH MENU DRIVEN SUBSCRIBER ACCESS and application Serial Number 08/160,280, filed December 2, 1993, entitled NETWORK CONTROLLER FOR CABLE TELEVISION DELIVERY SYSTEMS, now U.S. Patent No. 5,600,364.

The following patents and continuation-in-part applications, also based on the above-referenced patent application, are incorporated herein by reference:

U.S. Patent No. 5,798,785, entitled REPROGRAMMABLE TERMINAL FOR SUGGESTING PROGRAMS OFFERED ON A TELEVISION PROGRAM DELIVERY SYSTEM.

001950-11308

1 U.S. Patent No. 5,659,350, entitled AN OPERATIONS CENTER FOR A  
2 TELEVISION PROGRAM PACKAGING AND DELIVERY SYSTEM, dated August  
3 19, 1997.

4 U.S. Patent No. 5,734,83, entitled SET-TOP TERMINAL FOR CABLE  
5 TELEVISION DELIVERY SYSTEMS, dated March 31, 1998.

6 Ser. No. 08/160,194, entitled ADVANCED SET-TOP TERMINAL FOR CABLE  
7 TELEVISION DELIVERY SYSTEMS, filed December 2, 1993.

8 U.S. Patent No. 5,682,195, entitled DIGITAL CABLE HEADEND FOR CABLE  
9 TELEVISION DELIVERY SYSTEM, dated October 28, 1997.

#### 10 Background Of The Invention

11 The invention relates to television entertainment systems for providing television  
12 programming to consumer homes. More particularly, the invention relates to a method  
13 and an apparatus that allows subscribers to order broadcast digital television  
14 programming.

15 Advances in television entertainment have been primarily driven by  
16 breakthroughs in technology. In 1939, advances on Vladmir Zworykin's picture tube  
17 provided the stimulus for NBC to begin its first regular broadcasts. In 1975, advances  
18 in satellite technology provided consumers with increased programming to homes.

19 In addition to advances in television broadcast technology, government regulatory  
20 agencies have placed requirements on the broadcast television industry. In particular, the  
21 over-the-air broadcast television networks will soon transition to high definition  
22 television (HDTV) - a broadcast digital television standard. These broadcasters may elect  
23 to provide a single HDTV digital signal in their allotted bandwidth, with the remaining  
24 bandwidth used for standard definition television (SDTV) digital programming. While  
25 the broadcast networks may desire to structure some of these channels to include a  
26 subscription, or pay-per-view feature, no mechanism currently exists to allow the  
27 broadcast networks to control access to their future digital programming. Without an  
28 effective authorization and billing system, the broadcast networks will likely not

6           The present invention solves these problems so that over-the-air broadcast  
7 television services can be expanded to incorporate increased programming choices.

9 This invention relates to a digital television program delivery system.  
0 Specifically, the present invention is a digital television program delivery apparatus and  
1 method that provides subscribers with access to multiple channels of digital television  
2 programming including pay-per view-events. The invention incorporates advanced  
3 features such as menu-driven access and one-button-program-selection.

4           The invention makes use of developments in digital compression signaling that  
5           allows much greater throughput of television program signals over existing transmission  
6           media. These developments allow subscribers to use the invention to exploit a four-fold  
7           or more increase in current program delivery capability. In particular, the invention  
8           provides subscribers with a menu-driven access scheme to an expanded television  
9           program lineup, enabling subscribers to access and view selected programs using a user  
10          friendly interface.

This interface includes a remote control and a series of menus that may be sequenced by the subscriber using simple alpha, numeric and iconic character access keys, or by moving a cursor or highlight bar on the television screen. In this way, the subscriber can advance from one menu to the next with the press of a single button. Different television programs, grouped by category, for example, may be selected and accessed from each menu. The menus also allow for ordering subscriptions to speciality channels. Additionally, an interface is provided that allows for programs to be selected for viewing using the Internet. As a result, the invention provides subscribers with

1 convenient methods of choosing a program for viewing from hundreds of program  
2 offerings.

3 The invention may be used in at least two domains: delivery of the broadcast  
4 digital multiplex signal via terrestrial, over-the-air media; and delivery of the broadcast  
5 digital multimedia signal over an existing cable television system. Over-the-air delivery  
6 includes standard television broadcasts. Cable delivery systems include coaxial cable  
7 systems, fiber optic delivery systems, and telephone delivery systems (including T1 and  
8 T3 lines, Integrated Services Digital Network (ISDN) lines and Asymmetric Digital  
9 Subscriber Lines (ADSL)). In addition, programs may be provided by direct satellite  
10 broadcast, by wireless broadcasts, and by other wired means including local area  
11 networks.

12 To access the paid programming, an electronic program guide, program  
13 authorization system and billing system are used to provide a menu of available  
14 programming and to authorize receipt of programming and provide for payment by  
15 subscribers.

16 The electronic program guide may be provided as part of the broadcast from a  
17 national broadcaster. Alternately, the electronic program guide may be provided on an  
18 Internet web site. The electronic program guide may list discrete programs, series of  
19 programs, speciality channels, such as high definition television, and speciality programs,  
20 such as sports packages. A subscriber indicates a desired program to order by moving  
21 a cursor over the program, using a remote control, for example. The subscriber then  
22 operates a go button on the remote control to send an order signal to a remote location.  
23 Order signals may be sent to the national broadcaster, a broadcast affiliate, a local cable  
24 system, any other broadcast program provider, another remote location, and to the  
25 Internet web site.

26 In an embodiment, after receiving the order signal, an order and authorization  
27 system verifies that the subscriber is authorized to view the selected program, and sends  
28 an authorization signal to the broadcast program provider. The broadcast program  
29 provider then provides a local authorization code that is addressed to the terminal that

1 originated the order signal. Alternately, the broadcast program provider may provide the  
2 local authorization to a terminal different from the terminal that initiated the program  
3 order. In this alternative, the address and identification number of the terminal to receive  
4 the program must be provided by the terminal initiating the program order. This  
5 alternative allows a subscriber to order a program from a location other than his home,  
6 such as at a kiosk in a video rental store. This alternative also allows the subscriber to  
7 provide access to a program, such as an annual subscription to a speciality channel or a  
8 sports program package, to another subscriber, for example as a gift.

9 The local authorization code may be multiplexed with the digital programs being  
10 broadcast by the broadcast program provided. Alternately, the local authorization code  
11 may be supplied by a separate location such as the Internet web site.

12 These and other objects and advantages of the invention will become obvious to  
13 those skilled in the art upon review of the following description, the attached drawings  
14 and appended claims.

#### 15 Brief Description Of Drawings

16 Figure 1 is a diagram of a digital television broadcast environment.

17 Figure 2 is a diagram of the primary components of a cable television delivery  
18 system using the broadcast environment of Figure 1.

19 Figure 3 is a diagram of a terminal used in conjunction with the broadcast  
20 environment of Figure 1.

21 Figures 4a - 4c are diagrams of remote location reception options.

22 Figure 5 is a diagram of an operations center of the television delivery system of  
23 Figure 2.

24 Figures 6a-6c show embodiments of a local cable television delivery system.

25 Figure 7 shows a remote control for use in the broadcast environment of Figure  
26 1.

27 Figure 8 is an example of an electronic program guide for use with the broadcast  
28 environment of Figure 1.

1           Figures 9a-9c are examples of order and authorizations systems for use in the  
2 broadcast environment of Figure 1.

3           Figure 10 is an diagram of a digital television broadcast environment.

4           Figure 11 is an diagram of an alternate digital television broadcast environment.

5           Figure 12 is an diagram of yet another example of a digital television broadcast  
6 environment.

7           Figure 13 is a diagram of an authorization signal for use with the broadcast  
8 environment of Figure 1.

9           Figure 14 is a diagram of a smart card.

10          Figures 15a-d show examples of an electronic program guide for use in the  
11 broadcast program environment of Figure 1.

12          Figure 16 is a flow chart showing the operation of the broadcast environment of  
13 Figure 11.

14          Figure 17 shows a menu structure for use with the television program delivery  
15 system of Figure 2.

16          Figure 18a is a drawing of storage for on-screen menu templates and other  
17 graphics files stored in graphics memory of the set top terminal.

18          Figure 18b is a drawing showing the hierarchical storage of text in memory for  
19 the set top terminal.

20          Figure 18c is a drawing of a flow chart showing the steps required for the  
21 microprocessor to retrieve, combine and display a menu.

22          Figure 19 is a block diagram of the hardware components of the set top terminal.

23          Figure 20a is a perspective front view of a set top terminal.

24          Figure 20b is a perspective rear view of a set top terminal.

25          Figure 21 is a schematic of a card upgrade for a set top terminal.

26          Figure 22a is a drawing of a frame format for a program control information  
27 signal.

28          Figure 22b is a drawing of a frame format for a polling response from the set top  
29 terminal.

## 1 Disclosure Of Invention

### 2 A. Television Program Delivery System Description

#### 3 1. Broadcast Television Environment

4 Figure 1 shows a broadcast television environment 100 in which a broadcast  
5 program provider, such as a national broadcaster 110, provides digital multiplex  
6 television programming 111 to a broadcast affiliate 112. The programming 111 may be  
7 provided to the broadcast affiliate 112 by any suitable means. For example, the national  
8 broadcaster 110 may provide the programming 111 by satellite transmission using a  
9 satellite broadcast system 120. The satellite broadcast system 120 may include an uplink  
10 site 121, a satellite 122, and a downlink site 123. The satellite broadcast system 120 may  
11 transmit the programming 111 to the broadcast affiliate 112 and directly to terminals  
12 140, 141 and 142 at remote locations such as subscribers' homes, for example.

13 The broadcast affiliate 112 may provide digital multiplex television programming  
14 115 to intermediate locations such as local cable system 114 and an operations center  
15 202. Alternately, the broadcast affiliates 112 may provide the programming 115 directly  
16 to the terminals 140-142. The operations center 202 may provide the programming 115  
17 to the local cable system 114. The local cable system 114 that receives the programming  
18 115 may in turn provide the programming 115 to the terminals 140-142.

19 The terminals 140-142 may be any terminal capable of receiving digital television  
20 signals including digital televisions, digital set top boxes and personal computers, or any  
21 combination of these devices. The terminals 140-142 may receive the programming 115  
22 by cable, including coaxial cable and fiber optic cable, by telephone cable (including T1  
23 and T3 lines, Integrated Services Digital Network (ISDN) lines and Asymmetric Digital  
24 Subscriber Lines (ADSL)), and by satellite broadcast. Alternately, the terminals 140-142  
25 may receive the programming 111 directly from the national broadcaster 110 via the  
26 satellite broadcast system 120. For example, the terminal 142 receives direct broadcast  
27 satellite programming via a backyard antenna 143.

28 Also coupled to the terminals 140-142 may be an Internet 105. The Internet 105  
29 provides access to web sites such as web site 106. The web site 106 may supply online

1 services and data that may be displayed on a television (not shown) or a personal  
2 computer (not shown), for example. The Internet 105 may also connect to the broadcast  
3 affiliate 112 and the national broadcaster 110. The national broadcaster 110 may use the  
4 Internet 105 to post program menus and to provide a means for authorizing reception of  
5 pay-per-view broadcast programming and to receive payment for the programming. The  
6 use of the Internet 105 for these purposes will be described later in more detail.

7 Figure 2 shows an expanded cable television program delivery system 200 that  
8 dramatically increases programming capacity using compressed transmission of television  
9 program signals and specifically incorporates the digital multiplex programming 111  
10 from the national broadcasters 110.

11 In addition to the programming 111, subscribers are able to access an expanded  
12 television program package that includes other broadcast programming, video on  
13 demand, interactive services, including online services, data services and other  
14 programming. Subscribers view selected programs through a menu-driven access scheme  
15 that allows each subscriber to select individual programs by sequencing a series of  
16 menus. The menus may be sequenced by the subscriber using simple alpha-numeric and  
17 iconic character access or moving a cursor or highlight bar on the television display or  
18 the personal computer to access desired programs by simply pressing a single button,  
19 rather than recalling from memory and pressing the actual two or more digit numeric  
20 number assigned to a selection. Thus, with the press of a single button, the subscriber can  
21 advance from one menu to the next, or can select a program for viewing. In this fashion,  
22 the subscriber can sequence the menus and select a program from any given menu. The  
23 programs may be grouped by category so that similar program offerings are found on the  
24 same menu. Alternately, the programs may be arranged in the menu in a matrix fashion  
25 by channel and time/date of broadcast.

26 Subscribers are able to view the menu, or electronic program guide, of the  
27 programming 115 in a variety of formats. The electronic program guide may be  
28 broadcast by the national broadcaster 110 and displayed at the terminal 140. Alternately,  
29 the electronic program guide may be provided at the web site 106.



1           Figure 3 shows the terminal 140 in more detail. The terminal 140 includes a  
2           processor 161 that controls operation of components of the terminal 140. A display 162  
3           displays the programming provided by the national broadcaster 110. The display 162  
4           may be a CRT, a LCD, or any other device suitable for displaying digital television  
5           signals. A memory 163 stores programming instructions, terminal operating instructions,  
6           authorization signals, programming, including targeted advertisements, programs  
7           watched data, and other information related to receiving and watching broadcast  
8           programs. A communications interface 164 provides communications with remote  
9           locations, such as the national broadcaster 110 and the Internet 105 shown in Figure 1.  
10          The communications interface 164 may be a cable modem, a telephone modem, a  
11          wireless modem, a fiber optic connector, a broadcast satellite receiver, a radio frequency  
12          receiver, a LAN connector, or any other device capable of one or two-way  
13          communication between the terminal 140 and the remote location, or any combination  
14          of these devices. A receiver module 165 receives broadcast programming from the  
15          national broadcaster 110. The receiver module 165 may include one or more receivers.  
16          Alternatively, the functions of the receiver module 165 may be spread among other  
17          distributed equipment, such as a personal computer or smart card, for example. A tuner  
18          166, coupled to the receiver module 165, tunes to an appropriate channel to display a  
19          program provided by the national broadcaster 110. If the program is a pay-per-view  
20          program, it may be encrypted. A decrypter 167 decrypts such pay-per-view programs so  
21          that they may be displayed on the display 162. A command input device 168 sends  
22          commands to the processor 161. The command input device 168 may be a remote control  
23          or a data entry device included in the terminal 140. The command input device 168 may  
24          also be a remote device and a soft key board that is displayed on the display 162. A  
25          transmitter 169 transmits information, such as program order signals, via the  
26          communication interface 164 to the national broadcaster 110 or the Internet 105.

27          The terminal 140 also includes a demodulator 150, and a demultiplexer 159 to  
28          process the programming 115, a NTSC encoder to convert digital signals to NTSC  
29          standard, and a video output to produce video for display on the display 162. Other

1 components required to provide television programming at the terminal 140 are described  
2 later in more detail.

3 Some of the above features may be incorporated into the set top terminal 220, or  
4 may be added to the set top terminal 220 by use of a plug-in card, such that described in  
5 U.S. Patent 5,734,853, entitled SET TOP TERMINAL FOR CABLE TELEVISION  
6 DELIVERY SYSTEMS and in copending application Serial No. 08/160,194, entitled  
7 ADVANCED SET TOP TERMINAL FOR CABLE TELEVISION DELIVERY  
8 SYSTEMS, the disclosures of which are hereby incorporated by reference.

9 The terminal 140 may be embodied as a digital television with the above-  
10 described components built in. The terminal 140 may also be embodied as an analog or  
11 digital television with an attached set top terminal. The terminal 140 may further be  
12 embodied as a digital television that incorporates a smart card and that is coupled to a  
13 personal computer. Finally, the terminal 140 may be a digital television that incorporates  
14 a smart card alone. The terminal 140 may receive the programming over-the-air from the  
15 national broadcaster 110 or the broadcast affiliate 112, via a wired media such as by cable  
16 from the local cable system 114, and via the satellite broadcast system 120.

## 17 2. In-Home Reception Options

18 Figures 4a, 4b and 4c show reception options at the remote locations such as at  
19 a subscriber's home. In Figure 4a, a television 170 is coupled to a digital set top terminal  
20 220. The set top terminal 220 receives the programming 115 from the broadcast affiliate  
21 112 or the local cable system 114. The local cable system 114, using the cable headend  
22 208 or the operations center 202 shown in Figure 2, may provide expanded television  
23 programming for display on the television 170. Alternately, the broadcast affiliate 112  
24 may provide the programming 115 by use of the satellite broadcast system 120. In this  
25 alternative, the set top terminal 220 would be coupled to a local, or backyard, satellite  
26 dish antenna or similar device. In yet another alternative, the set top terminal 220  
27 receives programming from both the satellite broadcast system 120 and the local cable  
28 system 114.

1 Also shown in Figure 4a is a telephone 178 that may be used to communicate with  
2 the broadcast affiliate 112 and the cable headend 208, and a personal computer 172 and  
3 a modem 173 that may be used to communicate with the Internet 105. The personal  
4 computer 172 may be coupled to the set top terminal 220 via signal path 174. The signal  
5 path 174 may include a cable connection such as a RS-232 cable and connectors or by  
6 wireless means, such as infra red signaling and radio frequency signaling, for example.

7 The set top terminal 220 performs the necessary processing to send the  
8 programming 115 to the television 170 for display. For example, if the television 170 is  
9 an analog television, the set top terminal 220 may demultiplex the programming 115,  
10 convert the demultiplexed digital programming to a NTSC-compatible analog signal and  
11 provide the analog signal to the television 170. If the television 170 is a digital  
12 television, the set top terminal 220 may demultiplex the programming 115 and supply the  
13 demultiplexed signal to the television 170.

14 The set top terminal 220 may receive commands from a remote control 900. The  
15 remote control 900, which will be described in detail later, may be an infrared or a radio  
16 frequency control, or any other suitable control. The set top terminal 220 may include  
17 a variety of error detection, decryption, and coding techniques such as anti-taping  
18 encoding. The set top terminal 220 may include communication devices that allow  
19 reception and transfer of data with external sources such as the Internet 105. For  
20 example, the set top terminal 220 may include a telephone modem, a cable modem, a  
21 wireless modem, a fiber optic connector, a LAN connector, or any combination of these  
22 devices.

23 The set top terminal 220 has input and output ports for communication with other  
24 local and remote devices. For example, the set top terminal 220 may have an input port  
25 that receives information from the cable headend 208. The set top terminal 220 may have  
26 output ports that provide communications from the set top terminal 220 to the television  
27 170 and to a video cassette recorder (VCR) 175. Certain menu selections may cause the  
28 set top terminal 220 to send control signals directly to the VCR 175 to automatically  
29 program or operate the VCR 175. Also, the set top terminal 220 may contain a phone

1 jack that can be used for maintenance, trouble shooting, reprogramming and additional  
2 customer features. The phone jack may also be used to connect the set top terminal 220  
3 with the Internet 105. The set top terminal 220 may also contain stereo/audio output  
4 terminals and a satellite dish input port.

5 In an embodiment, the set top terminal 220 receives compressed program and  
6 control signals from the cable headend 208, the operations center 202, the broadcast  
7 affiliate 112, or the national broadcaster 110. After the set top terminal 220 receives the  
8 individually compressed program and control signals, the signals are demultiplexed,  
9 decompressed, converted to analog signals (if necessary) and either placed in local  
10 storage (for later display of for other control functions, such as creating programming  
11 menus), executed immediately, or sent directly to the television screen.

12 After processing certain signals received from the cable headend 208, the set top  
13 terminal 220 is able to store menu data for generating menus that are displayed on a  
14 subscriber's television. Before a menu is generated, menu templates may be created and  
15 sent to the set top terminal 220 for storage. A microprocessor in the set top terminal 220  
16 uses the control signals received from the operations center 202 or cable headend 208 to  
17 generate the menu templates for storage. Each menu template may be stored in volatile  
18 memory in the set top terminal 220. When the set top terminal 220 receives the menu  
19 template information, the set top terminal 220 demultiplexes the program control signals  
20 received from the cable headend 208 into four primary parts: video, graphics, program  
21 logic and text. Each menu template represents a different portion of a whole menu, such  
22 as a menu background, a television logo, a cursor highlight overlay, one or more scalable  
23 display windows, or other miscellaneous components needed to build a menu. The menu  
24 templates may be deleted or altered using control signals received from the operations  
25 center 202, the cable headend 208, the broadcast affiliate 112 or the national broadcaster  
26 110.

27 Once the menu templates have been stored in memory, the set top terminal 220  
28 can generate the appropriate menus. In an embodiment, the basic menu format  
29 information is stored in memory located within the set top terminal 220 so that the

1 microprocessor may locally access the information from the set top terminal 220 instead  
2 of from an incoming signal. The microprocessor next generates the appropriate menus  
3 from the menu templates and the other menu information stored in memory. The set top  
4 terminal 220 then displays specific menus on the subscriber's television that correspond  
5 to the inputs the subscriber selects. Alternately, menu viewing and program selection  
6 may use a web site on the Internet 105, which is accessed via the provided modem  
7 interface.

8 If the subscriber selects a specific program from the menu, the set top terminal  
9 220 determines on which channel the program is being shown, demultiplexes and extracts  
10 the single channel transmitted from the cable headend 208. The set top terminal 220 then  
11 decompresses the channel and, if necessary, converts the program signal to an analog  
12 NTSC signal to enable the subscriber to view the selected program. The set top terminal  
13 220 can be equipped to decompress more than one program signal. Two or more  
14 decompressors may be desirable to provide picture-on-picture capability, control signal  
15 decompression, enhanced channel switching or like features.

16 In addition to menu information, the set top terminal 220 may also store text  
17 transmitted from the remote location such as the cable headend 208 or the operations  
18 center 202. The text may inform the subscriber about upcoming events, billing and  
19 account status, new subscriptions, or other relevant information. The text may be stored  
20 in an appropriate memory location depending on the frequency and the duration of the  
21 use of the textual message.

22 Optional upgrades are available to enhance the performance of the set top terminal  
23 220. These upgrades may include a cartridge or computer card (not shown) that is  
24 inserted into an expansion slot in the set top terminal 220 or may include a feature offered  
25 by the cable headend 208 or operations center 202 to which the user may subscribe.  
26 Available upgrades may include online data base services, interactive multi-media  
27 services, access to digital radio channels, and other services.

1 In an embodiment, available converter boxes such as those manufactured by  
2 General Instruments or Scientific Atlanta, may be modified and upgraded to perform the  
3 functions of the set top terminal 220.

4 Figure 4b shows an alternate arrangement of components for receiving the  
5 broadcast digital programming 115. In Figure 4b, the digital television 171 is coupled  
6 to the broadcast affiliate 112 to receive the programming 115. The digital television 171  
7 may also receive the programming 115, and other programming, from the local cable  
8 system 114 or from the satellite broadcast system 120.

9 The digital television 171 may include a smart card 180 that performs the  
10 functions described above for the set top terminal 220. For example, the smart card 180  
11 may include a cable modem, a telephone modem, a wireless modem, a fiber optic  
12 connector, or a LAN connector. The smart card 180 is described later in more detail.  
13 Also shown in Figure 4b is the personal computer 172 and the modem 173, which  
14 function as before to connect to the Internet 105. The functions of the digital television  
15 171 may be controlled by the remote control 900, using either infrared signals or radio  
16 frequency signals, for example.

17 Figure 4c shows another arrangement of components for receiving the broadcast  
18 digital programming 115. In Figure 4c, a digital television 171' incorporating the smart  
19 card 180 receives the programming 115 from the local cable system 114. The television  
20 171' could also receive the programming via other media including direct satellite  
21 broadcast, fiber optic connections, local area network, such as an ethernet, the Plain Old  
22 Telephone Service (POTS), other telephone delivery systems (including T1 and T3 lines,  
23 Integrated Services Digital Network (ISDN) lines and Asymmetric Digital Subscriber  
24 Lines (ADSL)) and by over-the-air broadcast from the broadcast affiliate 112. The  
25 television 171', incorporating the smart card 180, includes some or all pf the functionality  
26 of the personal computer 172 shown in Figure 4b, for example. The television 171'  
27 connects to the Internet 105 and is able to access the web site 106 to view electronic  
28 program guides provided by the national broadcaster 110, the broadcast affiliate 112 or  
29 the local cable system 114. The television 171' is also able to access online services

provided by the Internet 105, and to perform computing functions normally associated with the personal computer 172. The remote control 900 may be used to control the television 171'. The television 171' may also, in its programming, include a soft key board 174 that is displayed on the display of the television 171'. The remote control 900 can then be used to operate "soft keys" on the soft key board 174. The television 171' may also incorporate a separate key board 174' that is used to control the television 171' and to operate the television 171' in its personal computer role. The key board 174' may be connected to the television 171' by a wired connection. Alternately, the key board 174' may communicate with the television 171' by wireless means including infra red signaling, radio frequency signaling and by other optical means including a laser. The television 171' may connect to other devices and media including the VCR 175 or other audio or video recording device, and to a telephone system via signal path 154. The television 171' may then be used to display information related to incoming telephone calls, such as a caller identification number, for example. The television 171' may also be used to support a video feed from a caller, such as in a video conference call.

### 3. Other System Components

Returning to Figure 2, the program delivery system 200 generally includes (i) at least one operations center 202, where program packaging and control information are created and then assembled in the form of digital data, (ii) a digital compression system, where the digital data is compressed, combined/multiplexed, encoded, and mapped into digital signals for satellite transmission to the cable headend 208 or the broadcast affiliate 112, and (iii) a set of in-home terminals. The program delivery system 200 transports the digital signals to the cable headend 208 where the signals are transmitted through a concatenated cable television system 210 or to the broadcast affiliate 112 where the programming 115 is sent to terminals, such as the terminal 141 of Figure 1, that are adapted to receive these signals. Within the cable headend 208, the received signals may be decoded, demultiplexed, managed by a local central distribution and switching mechanism, combined and then transmitted to the set top terminal 220 located in each subscriber's home over the cable system 210. Although concatenated cable systems 210

1 are the most prevalent transmission media for connecting to the home, telephone lines  
2 (including T1 and T3 lines, Integrated Services Digital Network (ISDN) lines and  
3 Asymmetric Digital Subscriber Lines (ADSL)), cellular networks, fiber optics, local area  
4 networks, Personal Communication Networks, and analog and digital satellites and  
5 similar technology for transmitting to the home can be used interchangeably with the  
6 program delivery system 200.

7 In the discussion that follows, the functions of the set top terminal 220 are  
8 described. These same functions may also be carried out by the digital television 171  
9 with the smart card 180, shown in Figure 4b, for example.

10 The program delivery system 200 has a reception region 207 with an in-home  
11 decompression capability. This capability is performed by a decompressor housed within  
12 the set top terminal 220. The decompressor remains transparent from the subscriber's  
13 point of view and allows any of the compressed signals to be demultiplexed and  
14 individually extracted from the composite data stream and then individually  
15 decompressed upon selection by the subscriber. The decompressed video signals may  
16 be converted into analog signals for television display. Such analog signals include  
17 NTSC and PAL formatted signals for use by a standard television. Control signals are  
18 likewise extracted and decompressed and then either executed immediately or placed in  
19 local storage such as a random access memory (RAM), a static random access memory  
20 (SRAM), a dynamic random access memory (DRAM), or other memory. Multiple sets  
21 of decompression hardware may be used to decompress video and control signals. The  
22 set top terminal 220 may then overlay or combine different signals to form the desired  
23 display on the subscriber's television. Graphics on video, picture-on-picture and split  
24 screen are examples of such a display.

25 Although a single digital compression standard (e.g., MPEG) may be used for  
26 both the program delivery system 200 and the concatenated cable system 210, the  
27 compression technique used may differ between the two systems. When the compression  
28 standards differ between the two media, the signals received by the cable headend 208  
29 must be decompressed before transmission from the headend 208 to the set top terminals



1 220. Subsequently, the cable headend 208 must recompress and transmit the signals to  
2 the set top terminal 220, which would then decompress the signals using a specific  
3 decompression algorithm.

4 The video signals and program control signals received by the set top terminal  
5 220 correspond to specific television programs and menu data that each subscriber may  
6 access through a subscriber interface. The subscriber interface is a device with buttons,  
7 such as a key pad, located on the set top terminal 220 or the portable remote control 900.  
8 In an embodiment, the subscriber interface is the combined alpha-character, numeric and  
9 iconic remote control 900, which provides direct or menu-driven program access. The  
10 remote control 900 also contains cursor movement and go buttons as well as alpha,  
11 numeric and iconic buttons. The remote control 900, used in conjunction with the menu  
12 arrangement, enables the subscriber to sequence through menus by choosing from among  
13 several menu options that are displayed on the television screen. In addition, the  
14 subscriber may bypass several menu screens and immediately choose a program by  
15 selecting the appropriate alpha-character, numeric or iconic combinations on the  
16 subscriber interface. In an embodiment, the set top terminal 220 generates the menus that  
17 are displayed on the television using the menu data and the menu templates, and the set  
18 top terminal 220 displays a specific menu or submenu option for each available video  
19 signal. In another embodiment, the menus are provided as a broadcast signal and are  
20 displayed on the television screen. In yet another embodiment, the menus are provided  
21 at a remote location, such as the web site 106 on the Internet 105, and subscribers may  
22 use the web site 106 for program selection.

23 4. Operations Center and Digital Compression System

24 The operations center 202 performs two primary services, packaging television  
25 programs and generating the program control information signal. At the operations center  
26 202, television programs are received from external program sources in both analog and  
27 digital form. Figure 5 shows an embodiment of the operations center receiving signals  
28 from various external sources 212. Examples of the external program sources are  
29 sporting events, children's programs, specialty channels, news or any other program

1 source that can provide audio or visual signals. Once the programs are received from the  
2 external program sources, the operations center 202 digitizes (and preferably compresses)  
3 any program signals received in analog form. The operations center 202 may also  
4 maintain an internal storage of programs. The internally stored programs may be in  
5 analog or digital form and stored on permanent or volatile memory sources, including  
6 magnetic tape or RAM or other suitable storage medium. Subsequent to receiving  
7 programming, the operations center 202 packages the programs into the groups and  
8 categories that provide the optimal marketing of the programs to subscribers. For  
9 example, the operations center 202 may package the same programs into different  
10 categories and menus for weekday, prime-time viewing and Saturday afternoon viewing.  
11 Also, the operations center 202 packages the television programs in a manner that enables  
12 both the various menus to easily represent the programs and the subscribers to easily  
13 access the programs through the menus.

14 The packaging of the digital signals may be performed at the operations center  
15 202 by computer assisted packaging equipment (CAP). The CAP system normally  
16 includes at least one computer monitor, keyboard, mouse, and standard video editing  
17 equipment. A programmer packages the signals by entering certain information into the  
18 CAP. This information includes the date, time slot, and program category of the various  
19 programs. The programmer and the CAP may use demographic data and ratings in  
20 performing the packaging tasks. After the programmer selects the various programs from  
21 a pool of available programs and inputs the requisite information, the programmer, with  
22 assistance from the CAP, can select the price and allocate transponder space for the  
23 various programs. After the process is complete, the CAP displays draft menus or  
24 program schedules that correspond to the entries of the programmer. The CAP may also  
25 graphically display allocation of transponder space. The programmer may edit the menus  
26 and transponder allocation several times until satisfied with the programming schedule.  
27 During the editing, the programmer may direct the exact location of any program name  
28 on a menu with simple commands to the CAP.

1           The packaging process also accounts for any necessary groupings by satellite  
2 transponder. The operations center 202 may send different groups of programs to  
3 different cable headends 208 and/or set top terminals 220. One way the operations center  
4 202 may accomplish this task is to send different program packages to each transponder.  
5 Each transponder, or set of transponders, then relays a specific program package to  
6 specific cable headends 208 and/or set top terminals 220. The allocation of transponder  
7 space is another important task performed by the operations center 202.

8           The operations center 202 may also "insert" directions for filling local available  
9 program time in the packaged signal to enable local cable and television companies to fill  
10 the program time with local advertising and/or local programming. Consequently, the  
11 local cable headends 208 are not constrained to show only programs transmitted from the  
12 operations center 202. New set top terminals may incorporate both digital and analog  
13 channels. Therefore, the cable headend 208 may combine analog signals with the digital  
14 signals prior to transmitting the program signals to the set top terminals 220.

15           After packaging the programs, the CAP creates a program control information  
16 signal to be delivered with the program package. The program control information  
17 signal contains a description of the contents of the program package, commands to be  
18 sent to the cable headend 208 and/or set top terminal 220, and other information relevant  
19 to the signal transmission.

20           In addition to packaging the program control information signal, the operations  
21 center 202 employs digital compression techniques to increase existing satellite  
22 transponder capacity by a 4:1 ratio, or more, resulting in at least a four-fold increase in  
23 program delivery capability. A number of digital compression algorithms currently exist  
24 which can achieve the resultant increase in capacity and improved signal quality desired  
25 for the system. The algorithms generally use one or more of three basic digital  
26 compression techniques: (1) within-frame (intraframe) compression, (2) frame-to-frame  
27 (interframe) compression, and (3) within carrier compression. For example, the MPEG  
28 2 compression method may be used. After digital compression, the program signals are

1 combined (multiplexed) and encoded. The combined program signal is subsequently  
2 transmitted to various uplink sites 204.

3 There may be a single uplink site 204 or multiple uplink sites (represented by  
4 204', shown in phantom in Figure 2) for each operation center 202. The uplink sites 204  
5 may either be located in the same geographical place or may be located remotely from the  
6 operations center 202. Once the combined program signal is transmitted to the uplink  
7 sites 204, the signal may be multiplexed with other signals, modulated, upconverted and  
8 amplified for transmission over satellite. Multiple cable headends 208 may receive such  
9 transmissions.

10 In addition to multiple uplinks 204, the delivery system 200 may also contain  
11 multiple operations centers 202. One method for using multiple operations centers 202  
12 is to designate one of the operations centers 202 as a master operations center and to  
13 designate the remaining operations centers 202 as slave operations centers. In this  
14 configuration, the master operations center coordinates various functions among the slave  
15 operations centers such as synchronization of simultaneous transmissions and distributes  
16 the operations workload efficiently.

#### 17 5. Cable Headend

18 After the operations center 202 has compressed and encoded the program signals  
19 and transmitted the combined program signals to the satellite, the cable headend 208  
20 receives and further processes the signals before they are relayed to each set top terminal  
21 220. Each cable headend site is generally equipped with multiple satellite receiver  
22 dishes. Each dish is capable of handling multiple transponder signals from a single  
23 satellite and sometimes from multiple satellites.

24 As an intermediary between the set top terminals 220 and the operations center  
25 202 (or other remote site), the cable headend 208 performs two primary functions. First,  
26 the cable headend 208 acts as a distribution center, or signal processor, by relaying the  
27 combined program signal to the set top terminal 220 in each subscriber's home. In  
28 addition, the cable headend 208 acts as a network controller 214 by receiving information

1 from each set top terminal 220 and passing such information on to an information  
2 gathering site such as the operations center 202.

3 Figure 6a shows an embodiment where the cable headend 208 and the  
4 subscriber's home are linked by certain communications media 216. In this particular  
5 embodiment, analog signals, digitally compressed signals, other digital signals and up-  
6 stream/interactivity signals are sent and received over the media 216. The cable headend  
7 208 provides such signaling capabilities in its dual roles as a signal processor 209 and a  
8 network controller 214.

9 As a signal processor 209, the cable headend 208 prepares the program signals  
10 that are received by the cable headend 208 for transmission to each set top terminal 220.  
11 In an embodiment, the signal processor 209 re-routes or demultiplexes and recombines  
12 the signals and digital information received from the operations center 202 and allocates  
13 different portions of the signal to different frequency ranges. Cable headends 208 which  
14 offer different subscribers different program offerings may allocate the program signals  
15 from the operations center 202 in various manners to accommodate different subscribers.  
16 The signal processor 209 may also incorporate local programming and/or local  
17 advertisements into the program signal and forward the revised program signal to the set  
18 top terminals 220. To accommodate this local programming availability, the signal  
19 processor 209 must combine the local signal in digital or analog form with the operations  
20 center program signals. If the local cable system uses a compression standard that is  
21 different than the one used by the operations center 202, the signal processor 209 must  
22 also decompress and recompress incoming signals so they may be properly formatted for  
23 transmission to the set top terminals 220. This process becomes less important as  
24 standards develop (i.e., MPEG 2). In addition, the signal processor 209 performs any  
25 necessary signal decryption and/or encryption.

26 As a network controller 214, the cable headend 208 performs the system control  
27 functions for the system. The primary function of the network controller 214 is to  
28 manage the configuration of the set top terminals 220 and process signals received from  
29 the set top terminals 220. In an embodiment, the network controller 214 monitors, among

1 other things, automatic poll-back responses from the set top terminals 220 remotely  
2 located at each subscribers' home. The polling and automatic report-back cycle occurs  
3 frequently enough to allow the network controller 214 to maintain accurate account and  
4 billing information as well as monitor authorized channel access. In this embodiment,  
5 information to be sent to the network controller 214 may be stored in RAM within each  
6 set top terminal 220 and will be retrieved only upon polling by the network controller  
7 214. Retrieval may, for example, occur on a daily, weekly or monthly basis. The  
8 network controller 214 allows the television program delivery system 200 to maintain  
9 complete information on all programs watched using a particular set top terminal 220.

10 In addition to the above, the network controller 214 allows the television program  
11 delivery system 200 to receive detailed information regarding operations at each set top  
12 terminal 220. This information includes click-stream data such as operation of channel  
13 select buttons, cursor buttons, volume adjust buttons, mute buttons, and other buttons on  
14 the remote control 900, for example.

15 The network controller 214 is also able to respond to the immediate needs of a set  
16 top terminal 220 by modifying the program control information signal received from the  
17 operations center 202. Therefore, the network controller 214 enables the television  
18 program delivery system 200 to adapt to the specific requirements of individual set top  
19 terminals 220 when the requirements cannot be provided to the operations center 202 in  
20 advance. In other words, the network controller 214 is able to perform "on the fly  
21 programming" changes. With this capability, the network controller 214 can handle  
22 sophisticated local programming needs such as, for example, interactive television  
23 services, split screen video, and selection of different foreign languages for the same  
24 video. In addition, the network controller 214 controls and monitors all compressors and  
25 decompressors in the system.

26 The television program delivery system 200 and digital compression provide a  
27 one-way path from the operations center 202 to the cable headend 208. Status and billing  
28 information may sent from the set top terminal 220 to the network controller 214 at the  
29 cable headend 208 and not directly to the operations center 202. Thus, program

1 monitoring and selection control may take place only at the cable headend 208 by the  
2 local cable company and its decentralized network controllers 214 (i.e., decentralized  
3 relative to the operations center 202, which is central to the television program delivery  
4 system 200). The local cable company will in turn be in communication with the  
5 operations center 202 or a regional control center (not shown) that accumulates return  
6 data from the set top terminal 220 for statistical or billing purposes. In alternative system  
7 embodiments, the operations center 202 and the statistical and billing sites are collocated.  
8 Further, telephone lines with modems may be used to transfer information from the set  
9 top terminal 220 to the statistical and billing sites. Alternately, the set top terminal 220  
10 may incorporate a cable modem, a wireless modem, connectors, LAN connectors, T1 and  
11 T3 connectors, Asymmetric Digital Subscriber Line (ADSL) Connectors, Integrated  
12 Digital Service Network (ISDN) connectors or other advanced communications interfaces  
13 for transmitting information upstream to the cable headend 208, the operations center  
14 202, a separate statistical and billing site, an Internet 105 web site, and other remote  
15 locations.

16 In the above discussion, the cable headend 208 was used to provide programming  
17 to the set top terminals 220. However, the national broadcaster 110 could choose to send  
18 the programming 111 directly to the terminal 142 of Figure 1 by satellite, for example.  
19 Optionally, the broadcast affiliate 112 could send the programming 115 directly to the  
20 terminal 140 or to the terminal 141.

21 Figure 6b shows the cable headend 208 having a file server 215 capable of storing  
22 digital compressed data. The cable headend components shown in Figure 2 include the  
23 network controller 214, the file server 215, signal reception equipment 234, an  
24 authorization component 236, and a set of channel modulators 238. The network  
25 controller 214 performs many of its functions using its interface 232 with the file server  
26 and its interface 268 with the authorization component 236 (which, in turn, is connected  
27 to the file server 215 over a separate connection or interface 235). The network controller  
28 214 and other cable headend components all work with one another to provide the  
29 capability to deliver programming in response to requests from subscribers. The signal

1 reception equipment 234 receives RF signals 222 (which may include both analog or  
2 digital broadcast signals and digital programming and control information signals), ATM  
3 data 226, and local feeds 224. The signal reception equipment 234 may: (i) place various  
4 signals in storage in the file server 215 in digitally compressed format, (ii) send certain  
5 signals to the channel modulators 238 for distribution over the cable distribution network  
6 210' and/or (iii) send other signals to the network controller 214 for processing.

7 In the embodiment shown in Figure 6b, the signal reception equipment bypasses  
8 the file server 215, sending broadcast signals 239 over connection 240 directly to channel  
9 modulator 238 for distribution to subscribers. The signal reception equipment 234 also  
10 transfers certain program control information and data to the network controller 214 over  
11 a control link or connection 242. In this way, the network controller 214 can receive the  
12 program control information signal from the operations center 202 or some other remote  
13 source through the signal reception equipment 234.

14 The authorization component 236 can receive requests for programs from the set  
15 top terminals 220 either by telephone line 244 or upstream data transmissions 246 over  
16 the cable distribution network 210'. The authorization component 236 processes the  
17 subscriber requests, prompting the file server 215 to spool the program requested by the  
18 subscriber. Alternatively, the file server 215 may be instructed to transmit an  
19 authorization code to the subscriber to enable descrambling or reception of a specific  
20 program by the subscriber's set top terminal 220. The network controller 214 monitors  
21 all incoming requests to the authorization component 236 in order to maintain up-to-date  
22 information on programs watched and viewing habits. By monitoring and coordinating  
23 with the authorization component 236 and the file server 215, the network controller 214  
24 oversees, and in some cases initiates, the selection, spooling and transmission of  
25 programs, menus and advertisements to the subscribers in the cable distribution network  
26 210'. The network controller 214 may also receive upstream data 246 directly.

27 Figure 6c shows a more detailed illustration of the cable headend 208 components  
28 with a file server 215 and network controller 214. As shown in the figure, the headend  
29 includes signal reception equipment 234, an authorization component 236, a file server



1 215, MPEG decoders 250, a buffer with frame repeat 252, channel modulators 238, and  
2 the network controller 214. The network controller 214 includes several components.  
3 These components include a receiver 254 or set of receivers 254 (including a  
4 demodulator 254', demultiplexer 254" and/or buffering circuitry 255), a work station 256,  
5 a program control information (PCI) signal processing capability 258, a network  
6 management central processing unit (CPU) 260, databases 262, control software 264 and  
7 an instruction memory 266 (which stores computer program instructions that may be  
8 executed by the network management CPU 260). These components are exemplary of  
9 the components that reside within the network controller 214; however, other  
10 components, such as additional storage (e.g., RAM, ROM, EPROM, and EEPROM),  
11 processors, work stations, receiver equipment, signal processing devices, and additional  
12 software may also be included in the network controller 214.

13 The network controller 214 uses such components in its coordination and  
14 management of cable headend 208 operations. For example, the network management  
15 CPU 260 is linked or connected to all other components in the network controller 214.  
16 The network management CPU 260 also includes connections or links, either directly or  
17 indirectly, with other cable headend 208 components.

18 As shown in Figure 6c, the network management CPU 260 is linked to the  
19 authorization component 236 through a data and signal interface 268 (which may be the  
20 same or an interface separate from the interface 235 shown in Figure 6c that connects the  
21 authorization component 236 with the file server 215). The network management CPU  
22 260 also coordinates and manages file server 215 functions through a separate interface  
23 232. These interfaces between the network management CPU 260, on the one hand, and  
24 the authorization component 236 and file server 215, on the other hand, may be direct or  
25 indirect through one or more interfaces. Such interfaces may be RS-232, RS-422, or  
26 IEEE-488 compatible. The network management CPU 260 also monitors and, in some  
27 instances, instructs the channel modulators 238 in regard to program distribution and  
28 signal processing activities over a separate connection or interface 269.

1           Within the network controller 214, the network management CPU 260 includes  
2           a number of internal connections, links, or interfaces. Such links, connections or  
3           interfaces include direct or indirect full duplex data and signal paths, including a  
4           connection 270 to receiver 254, a connection 272 to work station 256, a connection 274  
5           to the PCI signal processing equipment 258, a connection 276 with the data bases 262,  
6           a connection 278 with the instruction memory 266, a connection 280 with the control  
7           software 264, as well as other connections to additional internal components as described  
8           herein. The network management CPU 260 uses these links, connections, and interfaces  
9           to exchange data and program signals with other network controller components and  
10          devices. Using such components and devices, the network controller 214 performs its  
11          cable headend 208 operations.

12          The receiver 254 or set of receivers 254 is equipped to receive upstream data  
13          transmissions 246 from the subscriber. This receiver 254 or receivers 254 may simply  
14          be a telephone modem or more sophisticated control receiver equipment that is adapted  
15          to receive upstream data transmissions 246 directly from the cable distribution network  
16          210, 210' (Figures 2 and 6b). The network management CPU 260 coordinates such  
17          reception by the receiver 254 or receivers 254.

18          The PCI signal processing equipment 258 is interfaced with the cable headend  
19          208 signal reception equipment 234. The PCI signal processing equipment 258 enables  
20          the network controller 214 to receive the program control information signal from the  
21          operations center 202 or another remote site through an interface 242 with the signal  
22          reception equipment 234. The program control information signal is received by the  
23          network controller 214 and processed by the network management CPU 260 using the  
24          control software 264.

25          In some instances, the network management CPU 260 stores the data carried by  
26          the program control information signal. This data includes data on program packages and  
27          menu content and can be stored within the databases 262. The network controller 214  
28          can modify the program control information signal and transmit the modified program  
29          control information signal to those set top terminals 220 in the cable distribution network

1 210' that require the use of such data in order to generate menus or perform other local  
2 processing capabilities.

3 The databases 262 include a variety of databases in which data from upstream  
4 transmissions 246 from the subscribers can be stored. The databases 262 may also store  
5 information and data on program packaging, menu content, advertisements and billing.  
6 No set number of databases 262 are required for the network controller 214 to perform  
7 its operations, and a single temporary database may be used. In an embodiment,  
8 however, the network controller 214 uses several databases 262 that are accessed 278  
9 during network management operations.

10 The network management CPU 260 also acts with the instruction memory 266 as  
11 needed in order to run certain control and network management software 264. Such  
12 software may be stored in the instruction memory 266 or in one or more other storage  
13 locations within the network controller 214.

14 By maintaining links with the authorization component 236 and the file server  
15 215, the network controller 214 is flexible enough to maintain up-to-date programs  
16 watched information. Such programs watched information can be based on upstream  
17 data transmissions 246 that are received over the cable distribution network 210, 210' or  
18 through a telephone line 244. The network controller's 214 connection 232 with the file  
19 server 215 allows the network controller 214 to coordinate and manage intelligent  
20 selection and spooling of programs, menus and advertisements stored in the file server  
21 215. Alternatively, the software resident within the network controller 214 may reside  
22 within the file server 215 itself or certain functions may be split between the two cable  
23 headend components.

#### 24 6. Remote Control Device

25 The primary conduit for communication between the subscriber and the set top  
26 terminal 220 is through the subscriber interface, such as the remote control 900 shown  
27 in Figure 7. Through the remote control 900, the subscriber may select desired  
28 programming through the television program delivery system's menu-driven scheme or  
29 by directly accessing a specific channel by entering the actual channel number. Using the

1 remote control 900, the subscriber can navigate through a series of informative program  
2 selection menus. By using menu-driven, iconic or alpha-character access, the subscriber  
3 can access desired programs by simply pressing a single button rather than recalling from  
4 memory and pressing the actual channel number to make a selection. The subscriber can  
5 access regular broadcast and basic cable television stations by using either the numeric  
6 keys on the remote control 900 (pressing the corresponding channel number), or one of  
7 the menu icon selection options.

8 In addition to enabling the subscriber to easily interact with the television program  
9 delivery system 200, the physical characteristics of the subscriber interface 900 also adds  
10 to the user friendliness of the system. The remote control 900 easily fits in the palm of  
11 the subscriber's hand. The buttons of the preferred remote control 900 may contain  
12 pictorial symbols that are easily identifiable by the subscriber. Also, buttons that perform  
13 similar functions may be color coordinated and consist of distinguishing textures to  
14 increase the user friendliness of the system.

15 The remote control 900 may communicate with the set top terminal through  
16 wireless means such as infra red signals and radio frequency signals. In addition, the  
17 remote control 900 may communicate with the set top terminal by wired connections, and  
18 by other wireless means including laser-based optical signals that scatter the laser light  
19 at its source, microwave signals and masers. Laser links could be accompanied by a  
20 bidirectional radio frequency link to do automatic feedback control of the laser's pointing  
21 direction, with the laser slaved very tightly to the middle of the transmission beam width  
22 of the command interface in the set top terminal 220.

23 In the configurations shown in Figures 4a and 4b, the remote control 900 may be  
24 used to operate the set top terminal 220, the televisions 170 and 171 and the VCR 175.  
25 The remote control 900 may also be used to operate the PC 172 of Figures 4a and 4b. If  
26 the remote control 900 is not used to operate the PC 172 of Figures 4a and 4b, the PC 172  
27 may be operated by an attached keyboard (not shown) or some other suitable subscriber  
28 interface.

1 In addition to the remote control 900, the televisions 170, 171 and 177 of Figures  
2 4a and 4b, the VCR 175 and the PC 172 may be operated by voice communications. For  
3 example, the PC 172 and the set top terminal 220 may be trained to recognize and  
4 respond to the voice of the subscriber.

5 B. Broadcast Program Ordering System

6 The selection of a program from the programming 115 or the programming 111  
7 begins with the subscriber viewing a menu of program choices. Figure 8 shows an  
8 example of an electronic program guide 300 that is related to the programming 115. The  
9 program guide 300 could also be used to provide menu choice for programming provided  
10 directly by the national broadcaster 110 (i.e., programming 111 shown in Figure 1). As  
11 will be described later, the program guide 300 may also be incorporated into a menu-  
12 driven program access system provided by the cable headend 208 or the operations center  
13 202 of Figure 2. Alternately, the program guide 300 may be sent to the set top terminal  
14 220 over a dedicated channel, may be incorporated into other program signals, and may  
15 be provided at a remote location such as the web site 106 on the Internet 105.

16 Referring to Figure 8, the available programs are listed by title in a continuous  
17 time barker channel format. The program guide 300 lists the available programs in a  
18 matrix by time and channel. Thus, as shown in Figure 8, eight channels are available.  
19 Channel 1 is a free channel carrying HDTV programming. Channels 2 through 6 are pay-  
20 per-view channels carrying other standard definition digital programming. Channels 7  
21 and 8 are free channels and carry additional programming.

22 Each program in the program guide 300 could be identified by an event number  
23 that designates the time/date of broadcast, and by a program identifier, that uniquely  
24 identifies the program. The event data and the program identifier can be included in an  
25 authorization signal, or local authorization code, that is sent to the terminal 140.  
26 Alternately, the program identifier could be sent to the terminal 140, with an event  
27 number that allows the terminal 140 to access the selected program any time it was  
28 broadcast. In this arrangement, the terminal 140 may be manually tuned to the channel  
29 carrying the selected program.

1           The number of channels carrying standard definition digital programming can  
2 vary, depending on the total bandwidth allocated to the national broadcaster 110. In  
3 addition, if HDTV programming is not provided, for example during off-peak hours from  
4 midnight to 6 a.m., additional channels may be available for SDTV digital programs. The  
5 program guide 300 will change to accommodate the number of digital channels available.

6           The program guide 300 may be used to directly order desired programming. The  
7 desired program may be selected by using cursor keys on the remote control 900 to  
8 navigate the program guide 300 and to highlight programs listed in the program guide  
9 300. When the desired program is highlighted, the go button of the remote control 300  
10 may be operated to provide one-button ordering. That is, operation of the go button will  
11 send the order signal to the national broadcaster 110, for example.

12           The program guide 300 shown in Figure 8 includes a list of programs, available  
13 start times, costs to order and ratings. Other information may be included in the program  
14 guide 300. For example, for hit movies, the program guide 300 may include a brief  
15 description of the movie, its year of release, and the names of its major stars.

16           Other program guide configurations are also available. The program guide 300  
17 could be provided in a hard copy format. In this embodiment, the program guide 300  
18 could include alpha-numeric information that a subscriber would use to order a particular  
19 program. For example, a movie could be identified by an event number, that is the time  
20 and date of broadcast, and the duration of the broadcast, and by a program identifier that  
21 is unique to the movie. The event number and the program identifier could be included  
22 in the hard copy of the program guide 300. Other method for identifying a program or  
23 a series of programs are described in U.S. Patent 5,659,350 entitled OPERATIONS  
24 CENTER FOR A TELEVISION PROGRAM PACKAGING AND DELIVERY  
25 SYSTEM, which is hereby incorporated by reference. To order a program, the subscriber  
26 could enter the event number and the program identifier into the terminal 140, using the  
27 remote control 900, for example. By then pressing the go button on the remote control  
28 900, the subscriber would be sending a program order. Alternately, the subscriber could  
29 call an order and authorization system and provide the event number and program

1 identifier, or other descriptive information, over the telephone. The subscribers may also  
2 order a program by accessing an Internet web site, either from the set top terminal 220  
3 or the PC 172 of Figure 4a, for example. The order and authorization system would then  
4 issue an authorization signal. A corresponding local authorization code may be provided  
5 with the programming 115 or via the Internet web site.

6 The program guide 300 may include submenus and other features, which will be  
7 described later with respect to the menu-driven access system.

8 For real-time ordering and authorization, when the desired program is highlighted,  
9 the subscriber orders the program by operating a go, or select, button, on the remote  
10 control 900. Operation of the go button begins the process of program reception,  
11 program authorization and program payment. Specifically, operation of the go button  
12 sends the order signal to a remote location. In response, an authorization signal may be  
13 provided by the remote location that received the order signal, or another remote location.  
14 The authorization signal includes the code required to decrypt and display the selected  
15 program on the television 171 of Figure 4b, for example.

16 Ordering and authorization may also be conducted in a non-real-time basis. For  
17 example, the local cable system 114 or the broadcast affiliate 112 may conduct periodic  
18 polling over the cable system or the plain old telephone system (POTS) to determine  
19 recent selections. Programs selected by the subscriber would then be registered with the  
20 local cable system 114 or the broadcast affiliate 112 and a bill would be prepared  
21 reflecting the cost to the subscriber for accessing these programs. Alternately, the set top  
22 terminal 220 or the television 171 may incorporate a smart card/cash card with a pre-paid  
23 limit, where a quantity of purchases are pre-authorized. In another alternative, the  
24 programs are paid for after the fact upon the cash card being returned to an authorization  
25 and billing facility or billing agent.

26 The program guide 300 may be used to display program suggestions for discrete  
27 programs and events. The program guide may also be used to display multiple part  
28 programs, such as a television mini-series and subscriptions services. Subscription  
29 services could include speciality channels and speciality programs. The speciality

1 channels could include a first-run movie channel, for example. The speciality programs  
2 could include sporting events, for example. A subscription to the sporting events could  
3 be on a favorite team basis, a full season basis, or a partial season basis, for example.

4 The program guide 300 of Figure 8 may be displayed for viewing by the  
5 subscriber in a variety of telecommunications media. For example, the program guide  
6 300 may be provided as an electronic program guide (EPG) and carried on a television  
7 channel. The program guide 300 would then be displayed on the television 171.  
8 Alternately, the program guide 300 may be provided on a web site 106 of the Internet  
9 105. In this alternative, the program guide 300 could be displayed on the personal  
10 computer 172 or the television 171 of Figure 4b. Additional details of the electronic  
11 program guide for use with the broadcast environment of Figure 1 are provided later.

12 The electronic program guide could also be provided as an individualized  
13 program guide that is tailored to a specific subscriber or group of subscribers. That is,  
14 the individualized program guide could present a menu of favorite programs, where the  
15 menu of favorite programs is developed based on information gathered about the specific  
16 subscriber. The information could include subscriber-entered data that is provided by the  
17 subscriber to a series of questions presented at the terminal 140, for example. The series  
18 of questions may be presented when the specific subscriber initially accesses the  
19 broadcast environment, periodically thereafter, and at other times when desired by the  
20 specific subscriber. Gathering programs watched data is described in detail in copending  
21 application Serial No. 09/124,043 entitled METHOD AND APPARATUS FOR USING  
22 PROGRAMS WATCHED DATA, filed July 19, 1998, which is hereby incorporated by  
23 reference.

24 The programs watched data may be gathered by, or transferred to a processor in  
25 a remote location, such as the cable headend 208 and the broadcast affiliate 112, for  
26 example. The programs watched data may also be gathered by the set top terminal 220  
27 and then may be transferred to the processor in the remote location. The processor may  
28 also receive the demographic data, and the other subscriber specific data.



1 Individualized menus may be provided by the cable headend 208 or the national  
2 affiliate 112, with the menu data included in the programming 115, for example.  
3 Alternately, the menu data may be provided by out of band signaling.

4 When the electronic program guide is provided on the Internet web site, the  
5 Internet web site may recognize the subscriber, based on the subscriber's automatic  
6 number identification (ANI), user name, user identification, and Internet address (i.e.,  
7 REMOTE\_HOST, REMOTE\_ADDR, and HTTP\_NAME), for example. The subscriber  
8 may also be identified by a unique subscriber identifier that is provided to the subscriber  
9 upon subscribing to a broadcast television service. Other means for identifying a  
10 subscriber include special features such as browser cookies. A browser cookie is a  
11 mechanism that allows a web site server to store limited amounts of information on a  
12 browser. The information is typically information sent to a subscriber's terminal using  
13 a Set-cookie HTTP response field header. The Set-cookie field contains the cookie  
14 content as a name/value pair, and can also contain information explaining when the  
15 cookie will no longer be valid (expires), the Internet domain for which the cookie is valid  
16 (domain), and the path portion of the URL within this domain for which the cookie is  
17 valid. Browsers that understand cookies will store the data on the terminal's hard disk,  
18 for example, and will return these data to the web site server from which the cookie  
19 originated within a cookie request header field. Cookies are useful for storing state  
20 information (when the subscriber last visited the web site, which resources the subscriber  
21 last used, for example) on the browser, in such a way that the information is not lost when  
22 the subscriber leaves the web site or shuts down the browser.

23 A web site, such as the web site 106, may use cookies to customize program  
24 ordering for a subscriber. For example, the web site 106 may welcome a subscriber to  
25 the web site 106, based on the information in the cookie, and may navigate the subscriber  
26 to a preferred menu, or individualized program guide, based on previous program orders  
27 provided by the subscriber.

1 When the subscriber is identified, the web site 106 may create the individualized  
2 program guide, which the specific subscriber may download to the terminal 140 (i.e.,  
3 down load to the PC 172, the televisions 171 and 177 and the set top terminal 220).

4 Alternately, the subscriber may log on to the Internet web site, using the PC 172  
5 or the television 171' of Figures 4a-4c. The subscriber may then enter a subscriber  
6 identification. The Internet web site will then present the individualized menu to the  
7 subscriber, who may view the individualized menu on the television 171', for example.  
8 The individualized web site may be based on subscriber specific data, such as programs  
9 watched data, for example. The subscriber specific data may be stored in the set top  
10 terminal 220, for example, until a polling request message is sent to the set top terminal  
11 220, for example.

12 In the situations described above, the specific subscriber may also view a generic  
13 program guide, such as the program guide 300, by use of the remote control 900 or the  
14 PC 172 to enter a command to switch program guides. The specific subscriber may also  
15 view the individualized program guide, and select programs therefrom, by switching from  
16 the generic program guide to the individualized program guide.

17 The preceding discussion is based on the assumption that a subscriber initiates a  
18 program order from the subscriber's own terminal 140. However, the invention is not  
19 limited to this configuration. Alternately, the broadcast program provider may provide  
20 the local authorization code to a terminal different from the terminal that initiated the  
21 program order. In this alternative, an address and identification number of the terminal  
22 to receive the program, or some other means for identifying the terminal, such as the  
23 name and address of the individual to receive the program, must be provided by the  
24 terminal initiating the program order. This alternative allows the subscriber to order a  
25 program from a location other than his home, such as at a kiosk in a video rental store.  
26 This alternative also allows the subscriber to provide access to a program, such as an  
27 annual subscription to a speciality channel or a sports program package, to another  
28 subscriber, for example as a gift.

1           Figures 9a - 9c show alternate arrangements of an order and authorization system  
2           179 that can be used with the programming 111 or 115. In the discussion that follows,  
3           the subscriber receives the programming 115 from the local cable system 114. However,  
4           the order and authorization system 179 may also be used when the programming 115 is  
5           provided by the broadcast affiliate 112 or the satellite broadcast system 120, or any other  
6           entity capable of providing digital broadcast programs.

7           In Figures 9a - 9c, program order signals and program authorization signals may  
8           be provided over a variety of telecommunications media including via a cable modem to  
9           the local cable system 114; over a proprietary two-way transmission system to the local  
10          cable system 114; over a fiber optic cable system to the local cable system 114, the  
11          broadcast affiliate 112 or the national broadcaster 110; via a telephone modem with any  
12          of the local cable system 114, the broadcast affiliate 112 and the national broadcaster 110,  
13          using existing telephone lines; via a cellular modem over wireless telecommunication  
14          systems; via T1 and T3 lines, Asymmetric Digital Subscriber Lines, Integrated Digital  
15          Services Network lines, and via a telephone and the plain old telephone system (POTS).  
16          Alternately, the broadcast programs and the order and authorization signals may also be  
17          provided over a LAN such as an ethernet. In addition either the order signals and the  
18          authorization signals may be provided over the satellite broadcast system 120. An  
19          alternate arrangement for one-way authorization control is to embed the authorization  
20          signal in the programming 115 or the programming 111.

21          In Figure 9a, the national broadcaster 110 provides the programming 111 to the  
22          broadcast affiliate 112. The broadcast affiliate 112 sends the programming 115 to the  
23          local cable system 114. The local cable system 114 sends the programming 115 to the  
24          terminal 140. To decrypt and display a program from the programming at the terminal  
25          140, the subscriber must initiate the order signal. In the embodiment shown in Figure 9a,  
26          the subscriber sends an order signal 190 to the local cable system 114. Upon receipt of  
27          the order signal 190, the local cable system 114 sends an authorization signal 191 to the  
28          terminal 140. The authorization signal 191 includes a code that allows the terminal 140  
29          to decrypt the program ordered with the order signal 190.

1           Figure 9b shows an alternate arrangement of the order and authorization system  
2           179. The order and authorization system 179 shown in Figure 9b differs from that shown  
3           in Figure 9a in that an order signal 190' is sent to the broadcast affiliate 112, and in  
4           return, an authorization signal 193 is returned to the terminal 140.

5           Figure 9c shows yet another arrangement of the order and authorization system  
6           179. In Figure 9c, an order signal 190" is sent to the national broadcaster 110. The  
7           national broadcaster 110 then returns an authorization signal 195 to the terminal 140.

8           The arrangements of the order and authorization system 179 of Figures 9a - 9c  
9           show the authorization signal being sent by the same entity (e.g., the broadcast affiliate  
10          in Figure 9b) that received the order signal. The order and authorization system 179 is  
11          not limited to this configuration. For example, the order signal could be sent to the local  
12          cable system 114. The local cable system 114 could the relay the order signal to either  
13          the broadcast affiliate 112 or the national broadcaster 110. The broadcast affiliate 112  
14          or the national broadcaster 110, respectively, could then send the authorization signal to  
15          the terminal 140. In yet another arrangement, the national broadcaster 110 or the  
16          broadcast affiliate 112 could relay the authorization signal to the local cable system 114.  
17          The local cable system 114 would then send the authorization signal to the terminal 140.

18          In another example, although Figure 9a shows the order signal 190 being  
19          transmitted to the local cable system 114, the order signal 190 could also be transmitted  
20          to another remote location maintained by the local cable system 114, or maintained on  
21          behalf of the local cable system 114. For example, the order signal 190 could be  
22          transmitted to the web site 106 of the Internet 105. The local cable system 114 could  
23          maintain the web site 106. Alternately, the national broadcaster 110, the broadcast  
24          affiliate 112, or some other entity, such as an online television guide service, could  
25          maintain the web site 106.

26          In yet another alternative, a first terminal 140 could access the program guide 300  
27          and transmit an order signal 190, but designate the ordered program for display on a  
28          second terminal 140. In this alternative, address and identification information for the  
29          second terminal 140 would be provided with the order signal 190.

1 In still another embodiment, the order and authorization system 179 may provide  
2 local authorization codes for two or more programs that air at the same time. In this  
3 alternative, the terminal 140 may display the programs in a split screen or picture-in-  
4 picture format, may cycle between the two or more programs, may delay display of a  
5 program until a later showing is provided, may save one or more programs in memory  
6 for later replay, may direct an attached VCR or other video recording device to record one  
7 program while another is displayed, may display a first program on a first television and  
8 a second program on a second television, or any combination of the above features. For  
9 example, a terminal 140 could be authorized to view a package of live football games  
10 airing simultaneously. The terminal 140 could then cycle between games, or record one  
11 game and display a second game, for example. In order to accommodate these features,  
12 the terminal 140 may be provided with two or more tuners and associated processing  
13 components such as decompressors, demultiplexers and decrypters.

14 Figures 10, 11 and 12 show broadcast digital television environments that allow  
15 subscribers with different television reception capabilities to order and receive broadcast  
16 digital programming on a pay-per-view or subscription basis. Also shown in Figures 10-  
17 12 are terminals such as the terminal 140 of Figure 1. The terminals may have different  
18 capabilities. For example, one terminal could include an analog television 170 and a  
19 digital set top terminal 220 while another terminal 140 may include the digital television  
20 171 equipped with the smart card 171.

21 In the discussion that follows, the terminal 140 is used to refer generically to the  
22 different combinations of components. In Figures 10, 11 and 12, the programming is  
23 shown being supplied by a local cable system. However, as discussed above, the  
24 programming, and associated ordering, authorization and billing signals could also be  
25 provided by other telecommunications media including by satellite broadcast, over-the-air  
26 broadcast, wireless broadcast, fiber optic broadcast, T1 and T3 lines, ADSL and ISDN  
27 lines, and broadcast over POTS, individually and in combination.

28 Figure 10 shows a broadcast digital television environment 121 in which the  
29 network controller 214 of a local cable system 114 provides digital broadcast

1 programming to subscribers. The network controller 214, as the controller of the local  
2 cable system 114, receives the programming 115 from the broadcast affiliate 112, or  
3 directly from the national broadcaster 110. The network controller 214 provides  
4 programming 197, which may include a local authorization code 197', to subscribers of  
5 the local cable system 114. The programming 197 may be multiplexed and compressed.  
6 The local authorization code 197', which may also be multiplexed and compressed, is  
7 provided in response to an order placed by the subscriber, and is formatted such that it  
8 can be interpreted only by the terminal to which it is addressed. That is, the local  
9 authorization code 197' includes an address corresponding to the terminal that ordered  
10 the program. The address may be built into the circuitry of the terminal 140, or may be  
11 provided by the local cable system 114, for example.

12 The network controller 214 also supplies a program guide signal 198, which  
13 includes data related to available programs. The program guide signal 198 may also  
14 include instructions for formatting the data, such as a menu template. The program guide  
15 signal 198 is interpreted by the terminal 140 receiving it and is used to produce the  
16 program guide 300 shown in Figure 8, for example. The program guide 300 may include  
17 additional submenus, such as notification submenus, escape submenus, and description  
18 submenus. The submenus are described in detail later.

19 Subscribers to the local cable system 114 may receive the programming 197 and  
20 the program guide signal 198 in components that have different reception capabilities.  
21 In Figure 10, the set top terminal 220 receives the programming 197 and the program  
22 guide signal 198. The program guide signal 198 may be stored in a memory (not shown  
23 in Figure 10) of the set top terminal 220. Alternately, the program guide signal 198 may  
24 be provided on a real-time basis. Upon receiving a command to display the program  
25 guide 300, the set top terminal 220 formats the program guide signal 198 into a readable  
26 format such as that shown in Figure 8, and the television 170 displays the program guide  
27 300. The set top terminal 220 may demultiplex, decompress, and decrypt the program  
28 guide signal 198. The television 170 may be a digital television or an analog television.

1 If an analog television, the set top terminal 220 converts the digital data to a NTSC-  
2 compatible analog signal for display.

3 The set top terminal 220 receives program selections from the subscriber (e.g., by  
4 the subscriber operating the go button on the remote control 900). The set top terminal  
5 220 then produces the order signal 190 to order the selected program. The order signal  
6 190 may be provided over a cable television cable using a cable modem, a LAN, the  
7 POTS using a telephone modem, ADSL and ISDN, a fiber optic cable, and by wireless  
8 means using a wireless modem.

9 Also shown in Figure 10 is a digital television 171 that incorporates a smart card  
10 180. The smart card 180 receives the program guide signal 198, and produces the  
11 program guide 300 for display on the television 171. The television 171 receives the  
12 programming 197 with the local authorization code 197', as appropriate. The smart card  
13 180 receives program selections from the subscriber (e.g., by the subscriber operating the  
14 go button on the remote control 900). The smart card 180 then produces the order signal  
15 190 to order the selected program.

16 The order and authorization system 179, which may be located at the local cable  
17 system 114, a central billing location, or some other remote location including a web site  
18 on the Internet 105, receives the order signals 190 from the set top terminal 220 and the  
19 smart card 180. The order and authorization system 179 then prepares the authorization  
20 signal 191 and sends the authorization signal 191 to the network controller 214. On  
21 receipt of the authorization signal 191, the network controller 214 generates the local  
22 authorization code 197' that is addressed to the terminal from which the order signal  
23 originated, and multiplexes the local authorization code 197' into the programming 197.

24 The order and authorization system 179 also sends the authorization signal 191  
25 to a billing system 194. The billing system 194, on receipt of the authorization signal  
26 191, prepares a billing record that may be sent to the subscriber on a periodic basis. The  
27 billing record may also be used to debit a subscriber's account with the local cable system  
28 114, to debit a subscriber's checking account, or to charge to a subscriber's credit card,  
29 for example. If the program guide 300 incorporates an escape submenu (to be described

1 later), the billing record may not be generated by the billing system 194 until a set time  
2 after the start of the program. This feature allows the subscriber to cancel viewing of a  
3 program without incurring a fee, provided that a cancellation signal is received within the  
4 set time period, for example, five minutes. The subscriber can initiate the cancellation  
5 signal by accessing a hidden menu that incorporates this feature, for example.  
6 Alternately, the subscriber can cancel the order by manually tuning away from the  
7 channel displaying the selected program.

8 Figure 11 shows a broadcast digital television environment 131 in which the  
9 network controller 214 of the local cable system 114 provides digital broadcast  
10 programming to subscribers. The network controller 214, as the controller of the local  
11 cable system 114, receives the programming 115 from the broadcast affiliate 112, or the  
12 programming 111 directly from the national broadcaster 110. The network controller 214  
13 provides the programming 197, which may include the local authorization code 197', to  
14 subscribers of the local cable system 114. The local authorization code 197' is provided  
15 in response to an order placed by the subscriber, and is formatted such that it can be  
16 interpreted only by the terminal to which it is addressed. That is, the local authorization  
17 code 197' includes an address corresponding to the terminal that ordered the program.  
18 The address may be built into the circuitry of the terminal, or may be provided by the  
19 local cable system 114, for example.

20 The programming 197 may be received by subscribers having terminals with  
21 different reception capabilities. The set top terminal 220 receives the programming 197  
22 and may provide programs for display on the television 170. The television 170 may be  
23 a digital or an analog television. If an analog television, the set top terminal 220 converts  
24 the digital programs provided by the programming 197 into NTSC-compatible analog  
25 signals.

26 The digital television 177 also receives the programming 197. The digital  
27 television 177 displays those programs for which the local authorization code 197' is  
28 provided.



1           The digital television 171 equipped with the smart card 180 also receives the  
2 programming 197. The digital television 171 displays those programs for which the local  
3 authorization code 197' is provided.

4           As described above, the reception of the programming 197 is the same between  
5 the environment 121 shown in Figure 10 and the environment 131 shown in Figure 11.  
6 However, the reception of the program guide data and program ordering differ. In the  
7 environment 131, the subscribers view the national broadcaster's program selections by  
8 accessing the web site 106 on the Internet 105. That is, the national broadcaster 110 may  
9 create the web site 106, and provide the web site 106 with the program guide 300. The  
10 subscribers make program selections directly from the web site 106.

11           Referring to Figure 11, the set top terminal 220 is shown coupled to the web site  
12 106 over the signal path 147. The signal path 147 may be a coaxial cable or a telephone  
13 line, for example. The set top terminal 220 may be coupled to the web site 106 by a cable  
14 modem, a telephone modem, T1 and T3 lines, Integrated Services Digital Network  
15 (ISDN) lines and Asymmetric Digital Subscriber Lines (ADSL), a wireless modem or a  
16 fiber optic connector, for example. The display of the television 170 may be used as the  
17 display for viewing the web site 106. The remote control 900 may be used for sending  
18 commands to the set top terminal 220, which are then relayed to the web site 106 for  
19 selecting and ordering programs from the program guide 300. The web site 106 may also  
20 incorporate features such as a soft key board to increase its functionality.

21           Those skilled in the art will recognize many ways to access the web site 106. For  
22 example, the television 170 may display a web browser page that includes a location  
23 field. The web address may then be entered into the location field, using the remote  
24 control 900 or the key pad 221, and the go button of the remote control 900 operated to  
25 complete the connection to the web site 106. Alternately, the national broadcaster 110  
26 may provide an overlay or hidden menu (both of which will be described later) with a  
27 program that is currently being displayed on the television 170. The overlay menu or the  
28 hidden menu may contain a hypertext link to the web site 106. The remote control 900  
29 may then be used to select the hypertext link and the go button operated to activate the

1       hypertext link to the web site 106. The hypertext link may also be provided at other web  
2       sites on the Internet 105. The national broadcaster 110 may also provide a logo that  
3       overlays a broadcast program. In this case, the logo acts as a hypertext link. By selecting  
4       the logo, and operating the go button, the web site 106 may also be accessed.

5             In the above examples, the web site 106 may be displayed as a full screen display.  
6       Optionally, the web site 106 may be displayed in a separate window, or in a picture-in-  
7       picture format, so that the broadcast program continues to be displayed and seen on the  
8       television 170. The window containing the web site 106 display may be scaled or  
9       repositioned on the display of the television 170.

10            The web site 106 may include a single page listing the program choices in an  
11       electronic program guide, such as the program guide 300 shown in Figure 8. Alternately,  
12       the web site 106 may include multiple pages that are accessed through hypertext links or  
13       by operation of "forward", "back" and "home" buttons that are part of the web site 106  
14       display. The additional pages may contain additional program choices, when, for  
15       example, the number of choices exceed that which can be conveniently displayed on one  
16       page. The web site 106 may also include additional pages that provide program  
17       description information, program reviews, information regarding performers, and other  
18       related information.

19            The web site 106 may be used to directly order programs. For example, the order  
20       signal 190 may be generated by selecting a program from the program guide 300, and  
21       operating the go button of the remote control 900 to send the order signal 190 to the web  
22       site 106.

23            The smart card 180 is similarly connected to the web site 106. The smart card  
24       180 may incorporate a cable modem, a telephone modem, a wireless modem or a fiber  
25       optic connector, for example.

26            The subscriber using the digital television 177 may use the personal computer  
27       172, which is coupled to the modem 173, to access the web site 106 and to view the  
28       program guide 300 and order programs for display on the digital television 177. The  
29       computer 172 may communicate with the television 177 by wired or wireless means. In

1 Figure 12, the computer 172 is shown sending the local authorizations code 197' to the  
2 television 177 may be wireless. Wireless communication may be by infra red or radio  
3 frequency signaling, for example.

4 While the modem 173, the smart card 180, and the set top terminal 220 are all  
5 shown connecting to the web site 106 over the cable 147, the connection is not limited  
6 in this respect. The web site 106 may be accessed over a variety of different  
7 telecommunications systems such as the POTS, a coaxial cable, a fiber optic cable, T1  
8 and T3 lines, Integrated Services Digital Network (ISDN) lines and Asymmetric Digital  
9 Subscriber Lines (ADSL) or by wireless means.

10 The set top terminal 220, the smart card 180 and the modem 173 are all used to  
11 send the order signal 190 to the scheduling web site 106 and to view programs listed in  
12 the program guide 300. The order signal 190 indicates which program from the program  
13 guide is desired for viewing, and includes an address of the terminal requesting the  
14 program. When the scheduling web site 106 receives the order signal 190, it sends an  
15 authorization request 196 to the order and authorization system 179. The authorization  
16 request 196 includes an identity of the desired program and the address of the terminal  
17 requesting the program.

18 The order and authorization system 179 prepares an authorization signal 191 that  
19 is transmitted to the network controller 214. The network controller 214 produces the  
20 local authorization code 197' and multiplexes the local authorization code 197' with the  
21 programming 197. The network controller 214 then broadcasts the programming 197 to  
22 the terminal connected to the local cable system 114. Only those terminals that receive  
23 an authorization code with a matching address are able to decrypt and display the  
24 programming.

25 The order and authorization system 179 also sends the authorization request 196  
26 to the billing system 194. The billing system 194 generates a billing record, which may  
27 be used to bill the subscribers for programs watched.

28 The order and authorization system 179 may include an escape feature for pay-  
29 per-view events. For example, if a subscriber decides, after ordering a program, not to

1 watch the program, the subscriber may send a cancel program signal 192 to the web site  
2 106. Software incorporated in the web site 106 or the order and authorization system 179  
3 may include a time out feature. The time out feature allows the subscriber to view an  
4 ordered program for a short time, five minutes, for example, before the authorization  
5 request 196 is sent to the billing system 194.

6 If the subscriber sends the cancel program signal 192, the web site 106 or the  
7 order and authorization system 179 may generate a deauthorization signal 193. The  
8 deauthorization signal 193 is then sent to the terminal 140 that originated the cancel  
9 program signal 192. The deauthorization signal 193 can be multiplexed into the  
10 programming 197, or may be sent over the cable 147.

11 Figure 12 shows a digital television environment 144 in which a national  
12 broadcaster 110, a broadcast affiliate 112, or a local cable system 114 provides digital  
13 broadcast programming to subscribers, but program authorization is handled over the  
14 Internet 105. That is, the local authorization code 197' is provided from the web site 106  
15 to the terminal 140. The local authorization code 197' is based on an address built into  
16 the set top terminal 220, for example.

17 The programming 197 may be received by subscribers having terminals with  
18 different reception capabilities. The set top terminal 220 receives the programming 197  
19 and may provide programs for display on the television 170. The television 170 may be  
20 a digital or an analog television. If an analog television, the set top terminal 220 converts  
21 the digital programs provided by the programming 197 into NTSC-compatible analog  
22 signals.

23 The digital television 177 also receives the programming 197. The digital  
24 television 177 displays those programs for which the local authorization code 197' is  
25 provided.

26 The digital television 171 equipped with the smart card 180 also receives the  
27 programming 197. The digital television 171 displays those programs for which the local  
28 authorization code 197' is provided.

1 In the environment 144 shown in Figure 12, the subscriber both orders the  
2 programming 197 and receives authorization to view the programming 197 by signals  
3 sent to, and received from the web site 106, respectively. The electronic program guide,  
4 such as the program guide 300 shown in Figure 8, is also provided at the web site 106.  
5 That is, in the environment 144, the subscribers view the national broadcaster's program  
6 selections by accessing the web site 106 on the Internet 105. The national broadcaster  
7 110, the national affiliate 112, or the local cable system 114 may create the web site 106,  
8 and provide the web site 106 with the program guide 300. The subscribers then make  
9 program selections directly from the web site 106.

10 Referring to Figure 12, the set top terminal 220 is shown coupled to the web site  
11 106. The set top terminal 220 may be coupled by a cable modem, a telephone modem,  
12 a wireless modem, T1 and T3 lines, Integrated Services Digital Network (ISDN) lines and  
13 Asymmetric Digital Subscriber Lines (ADSL), for example. The display of the television  
14 170 may be used as the display for viewing the web site 106. The remote control 900  
15 may be used for sending commands to the set top terminal 220, which are then relayed  
16 to the web site 106 for selecting and ordering programs from the program guide 300. The  
17 web site 106 may also incorporate features such as a soft key board to increase its  
18 functionality.

19 The smart card 180 is similarly connected to the web site 106. The smart card  
20 180 may incorporate a cable modem, a telephone modem, a wireless modem or a fiber  
21 optic connector, for example.

22 The subscriber using the digital television 177 uses the personal computer 172,  
23 which is coupled to the modem 173 to access the web site 106 and to view the program  
24 guide 300 and to order programs for display on the digital television 177.

25 While the modem 173, the smart card 180, and the set top terminal 220 are all  
26 shown connecting to the web site 106 over the cable 147, the connection is not limited  
27 in this respect. The web site 106 may be accessed over a variety of different  
28 telecommunications systems such as the POTS, T1 and T3 lines, Integrated Services

1 Digital Network (ISDN) lines and Asymmetric Digital Subscriber Lines (ADSL) a  
2 coaxial cable, a fiber optic cable, or by wireless means.

3 The set top terminal 220, the smart card 180 and the modem 173 are all used to  
4 send order signals 190 to the scheduling web site 106 to view programs listed in the  
5 program guide 300. The order signal 190 indicates which program from the program  
6 guide 300 is desired for viewing, and includes an address of the terminal requesting the  
7 program. When the scheduling web site 106 receives the order signal 190, it sends an  
8 authorization request 196 to the order and authorization system 179. The authorization  
9 request 196 includes an identity of the desired program and the address of the terminal  
10 requesting the program.

11 The order and authorization system 179 prepares an authorization confirmation  
12 signal 196' that is transmitted to the subscriber's terminal, such as the set top terminal  
13 220. The national broadcaster 110, for example, broadcasts the programming 197 to the  
14 subscriber's terminals 140, such as the set top terminal 220. Only those subscriber's  
15 terminals 140 that receive the authorization confirmation signal 196' with a matching  
16 address are able to decrypt and display the programming.

17 The order and authorization system 179 also sends the authorization request 196  
18 to the billing system 194. The billing system 194 generates a billing record, which is  
19 used to bill the subscribers for programs watched.

20 The cable 147 may also be used for other communications with the web site 106.  
21 For example, if a subscriber decides, after ordering a program, not to watch the program,  
22 the subscriber may send a cancel program signal 192 to the web site 106. Software  
23 incorporated in the web site 106 or the order and authorization system 179 may include  
24 a time out feature. The time out feature allows the subscriber to view an ordered program  
25 for a short time, five minutes, for example, before the authorization request 196 is sent  
26 to the billing system 194.

27 If the subscriber does not send the cancel program signal 192, the web site 106  
28 or the order and authorization system 179 may generate a deauthorization signal 193.

1 The deauthorization signal 193 is then sent via the cable 147 to the terminal 140 that  
2 originated the cancel program signal 192.

3 The cable 147 may also be used to complete the program billing process. The  
4 billing system may send a debit signal (not shown) over the cable 147 to the terminal 140.  
5 The received debit signal debits a cash card (not shown) contained in the terminal 140.  
6 The cash card could be part of the smart card 180. The cash card may be removable or  
7 fixed to the smart card 180. Increases in value of the smart card 180 may also be  
8 accommodated over the cable 147. For example, the order and authorization system 179  
9 may send a credit signal (not shown) to the terminal 140, after the order and authorization  
10 system 179 receives a payment or electronic funds transfer from a subscriber.

11 The order and authorization system 179, or other remote location may send  
12 messages to terminals in the broadcast television environment 144. For example, the  
13 order and authorization system may send promotional messages to the terminal 140. The  
14 promotional messages may advertise upcoming programs or suggest purchase of special  
15 features such as a speciality sports program. The order and authorization system may  
16 send targeted advertisements to the terminal 140, where the targeted advertisements are  
17 selected based on a subscriber profile maintained in the local cable system 114, for  
18 example. Targeted advertising is described in detail in copending applications Serial No.  
19 08/735,549, entitled NETWORK CONTROLLER FOR CABLE TELEVISION  
20 DELIVERY SYSTEMS and in Serial No. 09/054,419, entitled TARGETED  
21 ADVERTISEMENT USING TELEVISION DELIVERY SYSTEMS, the disclosures of  
22 which are hereby incorporated by reference.

23 The terminals 140 may use the broadcast environment 144 for other  
24 communications purposes. For example, the terminals 140 shown in Figure 12 may send  
25 electronic mail to each other via the Internet 105, may access other web sites on the  
26 Internet 105 and may participate in multimedia conference calls, for example.

27 In an embodiment, program access information, in the form of the local  
28 authorization code 197' is provided to the terminal 140 from the national broadcaster 110,  
29 for example. Figure 13 shows the details of the local authorization code 197'. The local

1 authorization code 197' may be a frame format signal. The local authorization code 197'  
2 may include a leading flag 401 at the beginning of the signal, an address field 403, a  
3 terminal identifier 405, an information field 407 and a trailing flag 411 at the end of the  
4 signal.

5 The eight-bit flag 401 that appears at the beginning of the frame and the eight-bit  
6 flag 411 that appears at the end of the frame are used to establish and maintain  
7 synchronization. The eight-bit flag may be a "01111110" bit-stream. The address field  
8 403 designates a 4-bit address for a given terminal 140. The address field 403 may also  
9 include one or more routing indicators (not shown). The routing indicators may be used  
10 in the case where a signal, such as the local authorization code 197' must pass through  
11 several nodes of a telecommunications network. The terminal identifier 405 is a 16-bit  
12 field that uniquely identifies each terminal 140 with a 15-bit designation followed by an  
13 appended P/F bit 413. Although field size is provided by this example, a variety of sizes  
14 can be used with the present invention.

15 The information field 407 is variable in length. The variable length feature allows  
16 the local authorization code 197' to include a number of program authorizations, as  
17 shown in Figure 13. The information field 407 includes an eight-bit field 407' that  
18 contains an event number and a sixteen-bit field 407" that contains a program  
19 identification. The event number 407' may be formatted so that each time a particular  
20 program airs, the terminal 140 will be able to access the program. That is, the subscriber  
21 will only have to pay once to view the program for an indefinite number of showings in  
22 the future. The number of showings could be limited to those showing that occur in the  
23 current month, for example. The terminal 140 is able to access any program identified  
24 in the information field 407. Other methods for identifying programs are described in  
25 U.S. Patent 5,659,350, entitled OPERATIONS CENTER FOR A TELEVISION  
26 PROGRAM PACKAGING AND DELIVERY SYSTEM, which is hereby incorporated  
27 by reference.

28 The P/F bit 413 may be used to command a polling response from the terminal  
29 140 addressed, as described below. The P/F bit may be used to command the terminal



1 140 to provide a response back to the national broadcaster 110, for example. Such a  
2 response could command the terminal to report programs watched information, for  
3 example, that is stored in a memory of the terminal 140. The programs watched  
4 information could be used by the billing system 194 of Figures 10-12 to generate the  
5 billing record. The programs watched information could also be used for other purposes  
6 such as targeted advertising. Collection of such programs watched data is described in  
7 U.S. Patent 5,600,364, entitled NETWORK CONTROLLER FOR CABLE  
8 TELEVISION DELIVERY SYSTEMS, and in copending application Serial No.  
9 09/124,043, entitled METHOD AND APPARATUS FOR GATHERING PROGRAMS  
10 WATCHED DATA, the disclosures of which is hereby incorporated by reference.

11 In an embodiment, the local authorization code 197' is received by the terminal  
12 140 shown in Figure 3 and may be stored in the memory 163. When a subscriber tunes  
13 the terminal 140 to a broadcast digital channel, the processor 161 will then compare the  
14 local authorization code 197' to the programming 197 to determine if the subscriber is  
15 authorized to view the selected program. If authorization is granted, the processor 161  
16 then directs the decrypter 167 to decrypts the selected program and displays the decrypted  
17 program on the display 162 of the terminal 140.

18 In another embodiment, the processor 161 will instruct the tuner 166 to tune to  
19 the channel carrying the authorized program at some time prior to the start of the  
20 authorized program. For example, the tuner 166 may tune to the channel carrying the  
21 authorized program one minute prior to the start of the program. The processor 161 may  
22 be programmed by the subscriber to execute commands upon the occurrence of certain  
23 events. For example, the processor 161 may be programmed to instruct an attached  
24 recording device to record a program using a "tape program" command. If the subscriber  
25 has chosen "tape program," the processor 161 will begin recording the program on the  
26 attached VCR or other recording device at the start of the authorized program. If the  
27 display 162 of the terminal 140 is off, and the subscriber has chosen "turn on television,"  
28 the processor 161 will turn on the display 162. If the subscriber has not chosen "turn on  
29 television," and the television is off, but the "tape program" command is pending, the

1 processor 161 will instruct the VCR, or other recording device, to begin recording the  
2 program at the start of the selected program. The processor 161 may also be programmed  
3 to pause, or stop, recording, during commercial breaks, if any, in the programming 197.  
4 Recording of the program ends when the program is complete. The processor 161 may  
5 then return the tuner 166 to the channel previously selected, if a free channel, tune to the  
6 next authorized program, or tune to a menu channel that provides the program guide 300.

7 Figure 14 is a diagram of the smart card 180 that may be incorporated into the  
8 terminal 140 of Figures 4a-4c. For example, the smart card 180 may be incorporated into  
9 the television 171 of Figure 4b or the television 177 of Figure 4c. A microprocessor 181  
10 controls all the functions of the smart card 180. A communications interface 183  
11 provides communications with external sources such as a personal computer or a digital  
12 camera (not shown) through a RS-232 cable and connector (not shown), for example.  
13 The communications interface 183 may also be used to connect to the national  
14 broadcaster 110, or wireless means such as infra red or radio frequency signaling, for  
15 example. For communications with the national broadcaster 110, the communications  
16 interface 183 may include one or more of a one-way cable modem, a two-way cable  
17 modem, a telephone modem, a wireless modem, an ethernet connector, or a fiber optic  
18 connector, for example. A memory 185 stores programming instructions for the  
19 microprocessor 181 and data provided by devices external to the smart card 180. The  
20 memory 185 may be a RAM, a SRAM, a SDRAM, an EEPROM or other suitable  
21 memory device. A connector 187 provides external communications with components  
22 of the set top terminal 220.

23 The programming instructions in the memory 185 may be updated by loading  
24 programming instructions from the local cable system 114, the broadcast affiliate 112,  
25 or the national broadcaster 110. The programming instructions may also be loaded from  
26 the web site 106. Thus, if the broadcast associate 112, for example, changes the way in  
27 which the programming 115 is provided, the broadcast associate 112 may send  
28 programming instructions along with the programming 115 to the terminals 140. The

1 changed programming instructions may replace or modify programming instructions that  
2 are stored in the memory 185.

3 Also shown in Figure 14 is a data storage device 189. The data storage device  
4 189 may be removable, or may be affixed permanently to the smart card 180. The data  
5 storage device 189 may store program control information, program information, and  
6 subscriber specific data, for example. Program control information may be used to  
7 generate menu information for currently available programs. The program control  
8 information may also be used to control display of programs on the television 171. The  
9 program information may be a preview of an upcoming program, or may be the entire  
10 program or a portion of the entire program. For example, the first five minutes of all pay-  
11 per-view movies that are available in a given month may be stored in the data storage  
12 device 189. In this embodiment, once a program is selected, and authorized, the first part  
13 of the program is displayed, and the remaining portion of the program is supplied by the  
14 national broadcaster 110.

15 The smart card 180 may also include a cash card module (not shown). The cash  
16 card may be fixed or removable. The cash card may receive credits and debits from a  
17 remote locations such as the order and authorization system 179 and the billing system  
18 194.

19 The data storage device 189 may also store entire programs. For example, the  
20 data storage device 189 may store one or more movies. In addition, the data storage  
21 device 189 may store advertisements, including advertisements targeted to the subscriber.  
22 Targeted advertising is described in detail in copending applications Serial No.  
23 08/735,549, entitled NETWORK CONTROLLER FOR CABLE TELEVISION  
24 DELIVERY SYSTEMS and in Serial No. 09/054,419, entitled TARGETED  
25 ADVERTISEMENT USING TELEVISION DELIVERY SYSTEMS the disclosures of  
26 which are hereby incorporated by reference.

27 The data storage device 189 may be programmed to record programs watched data  
28 and click stream data. The programs watched data may be used to target the  
29 advertisements and as part of a billing and account system. Data recorded on the data

1 storage device 189 may be provided to a remote location such as the local cable company  
2 114 in response to a polling request message. Alternately, the data storage device 189  
3 may provide data to a remote source through another data transfer scheme such as carrier  
4 sense multiple access with collision detection/collision avoidance (CSMA/CD). Finally,  
5 the data storage device 189 may be taken to, or sent to the local cable company 114, for  
6 example, where its contents are read.

7 C. Menu System for Broadcast Program Ordering

8 A broadcast provider, such as the national broadcaster 110 may provide a menu  
9 of available programs, in the form of an electronic program guide (EPG). The program  
10 guide may be provided on a broadcast channel, and is displayed at the terminal 140 so  
11 that a subscriber can select a program for viewing. The program guide may also be  
12 provided at the web site 106 on the Internet 105. Finally, rather than an electronic  
13 program guide, the menu may be provided in a hard copy format, with program codes  
14 listed.

15 When the program guide is broadcast by the broadcast provider, the program  
16 guide may be displayed on a subscriber's television. This situation is shown in Figure  
17 10. In particular, the set top terminal 220 and the smart card 180 may receive the  
18 program guide. In this embodiment, the program guide may be provided as program data.  
19 One or more program guide templates may then be used in the set top terminal 220 and  
20 the smart card 180 to generate the program guide. Details for generating the program  
21 guide, or menu, using the program guide data and the template are provided later.  
22 Alternately, the program guide may be provided by the broadcast provider and displayed  
23 directly on the television 170 and the television 171.

24 When the program guide is provided on the web site 106, the program guide may  
25 be downloaded to the subscriber's computer, such as the personal computer 172, shown  
26 in Figure 11. The program guide may also be downloaded to the set top terminal 220 and  
27 the smart card 180 shown, for example in Figure 11, and may be displayed on the  
28 television 170 and the television 171, respectively.

1           An entire listing of available programs versus time of viewing may be too large  
2 to be easily displayed on a television display. The program guide 300, shown in Figure  
3 8, may therefore be scrolled using the cursor keys of the remote control 900, for example,  
4 to allow the display of future television programming. For example, the program guide  
5 300 may be scrolled to display television programming scheduled for viewing eight hours  
6 or 24 hours in the future. If the number of available channels is also too large to be easily  
7 displayed, the channels may also be scrolled using the cursor keys of the remote control  
8 900.

9           Figures 15a-15d are alternate examples of electronic program guides that may be  
10 used with the broadcast environment of Figure 1. Figure 15a shows an alternate program  
11 guide 310 that lists available program choices. In Figure 15a, an upper window 311  
12 identifies the program provider, such as the national broadcaster 110. Additional  
13 information such as time and date information may also be provided in the upper window  
14 311. Finally, a hypertext link or logo (shown in Figure 15 a as a star), or hot button to  
15 a web site may be included in the upper window 311. The web site may contain  
16 additional information about the program provider, preview information regarding  
17 upcoming programs, special features such as a package of NFL games that a subscriber  
18 can purchase, promotional programs and other advertising. A central window 313  
19 displays program choice information. For example, the central window 313 could display  
20 available programs by title. The control window 313 could also include additional  
21 information such as program rating, next available viewing time, and channel number,  
22 for example. A lower window 315 may contain access buttons that allow the subscriber  
23 to access other submenus or menus related to the program guide 310. For example, the  
24 lower window could include a "go back" button that returns the subscriber to the previous  
25 menu, a "forward" button that sends the subscriber to the next submenu in the sequence  
26 of menus, if available, a "return to program" button that returns the display to the last  
27 selected channel, and an interactive button that allows the subscriber to access interactive  
28 services including access to the Internet 105 and other online services, and Internet  
29 service providers.

Alternately, operation of the go button may cause a submenu to be displayed. Figure 15b shows an order submenu 320 that is displayed when the go button of the remote control 900 is operated. The order submenu 320 includes a program description window 321 that may provide a textual description of the selected program. The window 321 may also display a video clip or a still image related to the selected program. Additional windows, or banners may also be incorporated into the order submenu 320. A top window 322 may provide additional program information such as rating, start and stop times of broadcast, and current time and date information, for example. A bottom window 323 may incorporate soft keys and text that prompt the viewer to select one of order program or return to the program guide 310. The bottom window 323 may also include additional features, by way of soft keys, such as automatic "tune to program channel," "turn television on," and "record program button." Referring to Figure 3, the "automatic tune" command causes the tuner 166 to be tuned to the appropriate broadcast channel prior to the start time of the program, for example, one minute prior to start. Alternately, the processor 161 may create a virtual channel prior to the program start, and cause the tuner to tune to the virtual channel just prior to the program start. If the television is off at the time of the program start, the command "turn television on" causes the processor 161 to turn the television on so that the selected program may be viewed. The command "record program", if selected, may cause the processor 161 to begin recording the program on a VCR or other suitable recording device, for example. The television need not be on for the record program order to be executed. In this case, the processor 161 either creates a virtual channel, or causes the tuner to tune to the appropriate broadcast channel just prior to the start of the program. The order submenu 320 may also incorporate a feature that allows viewing of a program at one of several start times, as selected by the viewer. For example, a movie broadcast on a channel may be shown every three hours throughout a day, and the viewer has the option of selecting a start time. Alternately, the viewer may select a program for viewing, and be authorized to view the program at any time of the day. In this alternative, the viewer may select the time that recording occurs.

1 While the above features may be incorporated into a window of the order  
2 submenu, one or more of the features may also be incorporated into another submenu,  
3 such as a confirm order submenu 330 shown in Figure 15c.

4 In another embodiment, the electronic program guide may be displayed as a  
5 channel lineup menu 340 as shown in Figure 15d. In Figure 15d, programs are listed in  
6 a column format with the associated broadcast channel indicated. This allows some  
7 subscribers to manually tune to a particular channel to receive a program.

8 The channel lineup menu 340 includes program titles and may include program  
9 ratings, times of broadcast start, length of program and cost, for example. A subscriber  
10 selects a desired program by scrolling through the program list using the scroll buttons  
11 on the remote control 900. When the scrolling stops, the program is highlighted on the  
12 menu. The subscriber may then order the selected program by operating the go button  
13 on the remote control 900. Referring to Figure 10, for example, operation of the go  
14 button sends the order signal 190 to the order and authorization system 179. The order  
15 and authorization system 179 acts on the order signal 190, sending the local authorization  
16 code 197'. The terminal 140 that initiated the order signal 190 receives the local  
17 authorization code 197', which includes the address and identification of the terminal 140  
18 that sent the order signal 190. The local authorization code 197' may be stored in the  
19 memory of the terminal 140, or may be used immediately to access the authorized  
20 program.

21 D. Operation of the Broadcast Program Ordering System

22 Figure 16 is a flow chart of the major steps associated with ordering and receiving  
23 a pay-per-view program, and the subsequent billing cycle. The flow chart assumes the  
24 broadcast environment 131 of Figure 11.

25 The process begins with step S100. In step S110, the set top terminal 220  
26 accesses the web site 106. The web site 106 may be accessed by entering the address of  
27 the web site 106 into a location window of a web browser, by activating a hypertext link  
28 provided during the broadcast of current programming, and by activating a hypertext link  
29 received from a different web site. The process then moves to step S120.

1 In step S120, a data signal showing the web site 106 home page is transmitted to  
2 the set top terminal 220, and the web site 106 home page is displayed on the display of  
3 the television 170. The process then moves to step S130. In step S130, the web site 106  
4 receives the order signal 190 for a program selected by a subscriber. The order signal 190  
5 includes a program identifier and the address and identification of the set top terminal  
6 220. The process then moves to step S140.

7 In step S140, the web site 106 transmits the authorization request 196 to the  
8 ordering and authorization system 179. The process then moves to step S150. In step  
9 S150, the order and authorization system 179 determines if the set top terminal from  
10 which the order signal 190 originated is authorized to receive the selected program. The  
11 order and authorization system 179 may compare the rating of the selected program to  
12 a preset rating limit provided by the subscriber, for example. The order and authorization  
13 system 179 may determine if the subscriber's account is delinquent. If the set top  
14 terminal 220 is not authorized to receive the selected program, the process moves to step  
15 S160. Otherwise, the process moves to step S170.

16 In step S160, the order and authorization system 179 sends a message to the set  
17 top terminal 220 stating that the selected program cannot be accessed, along with the  
18 reason for no access. The process then moves to step S260 and ends.

19 In step S170, the order and authorization system 179 sends an authorization signal  
20 191 to the network controller 214. The process then moves to step S180. In step S180,  
21 the network controller 214 multiplexes the local authorization code 197' with the  
22 programming 197. The process then moves to step S190. In step S190, the set top  
23 terminal 220 receives the local authorization code 197' and stores the local authorization  
24 code 197' in the memory of the set top terminal 220. The process then moves to step  
25 S200.

26 In step S200, the set top terminal 220 tunes to the channel carrying the program  
27 for which the authorization signal applies. The program is then displayed on the display  
28 of the television 170. The process then moves to step S210. In step S210, the order and  
29 authorization system 179 starts a time out, with the beginning of the time out



1 corresponding to the start time of the displayed program. The process then moves to step  
2 S220. In step S220, the time out has ended, and the order and authorization system 179  
3 determines if a cancel program order 192 has been received from the set top terminal 220.  
4 If the cancel program order 192 has been received, the process moves to step S230.  
5 Otherwise the process moves to step S250.

6 In step S230, the order and authorization system 179 sends a cancel program  
7 signal 191" to the network controller 214. The process then moves to step S240. In step  
8 S240, the network controller 214 sends a deauthorization signal 193 to the set top  
9 terminal 220, and the set top terminal 220 tunes away from the now deauthorized  
10 program. The process then moves to step S260 and ends.

11 In step S250, the time out has been completed without receipt of a cancel program  
12 order 192, the order and authorization system 179 send a billing record to the billing  
13 system 194. The process then moves to step S260 and ends.

14 E. Menu-Driven Program Selection

15 In a broadcast television environment, a menu-driven program selection scheme  
16 may provide the subscriber with one-step access to all major menus, ranging from hit  
17 movies to sport specials to specialty programs. From any of the major menus, the  
18 subscriber can in turn access submenus and minor menus by cursor or alpha-character  
19 access.

20 Different types of menus may be used in the broadcast television environment.  
21 These menus include Program Selection menus and During Program menus. The first  
22 series of menus, Program Selection menus, consists of an Introductory menu, a Home  
23 menu, Major menus, and Submenus. The second series of menus, During Program  
24 menus, consists of two primary types, Hidden menus and the Program Overlay menus.

25 Immediately after the subscriber turns on the set top terminal 220, or the  
26 television 170 of Figure 10, for example, the Introductory menu welcomes the subscriber  
27 to the system. The Introductory menu may display important announcements from the  
28 local cable system 114 shown in Figure 1, advertisements from the national broadcaster  
29 110, or other types of messages. In addition, the Introductory menu can inform the

1 subscriber if the cable headend 208 has sent a personal message to the subscriber's  
2 particular set top terminal 220.

3 After the Introductory menu has been displayed the subscriber may advance to the  
4 next level of menus, namely the Home menu. In an embodiment, after a certain period  
5 of time, the menu system will advance by default to the Home menu. From the Home  
6 menu, the subscriber is able to access all of the programming options. The subscriber  
7 may either select a program directly by entering the appropriate channel number from the  
8 remote control 900, or the subscriber may sequence through incremental levels of menu  
9 options starting from the Home menu. The Home menu lists categories that correspond  
10 to the first level of menus called Major menus.

11 If the subscriber chooses to sequence through subsequent menus, the subscriber  
12 will be forwarded to the Major menu that corresponds to the chosen category from the  
13 Home menu. The Major menus further refine a subscriber's search and help guide the  
14 subscriber to the selection of his choice.

15 From the Major menus, the subscriber may access several submenus. From each  
16 submenu, the subscriber may access other submenus until the subscriber finds a desired  
17 television program. Similar to the Major menu, each successive level of Submenus  
18 further refines the subscriber's search. The system also enables the subscriber to skip  
19 certain menus or submenus and directly access a specific menu or television program by  
20 entering the appropriate commands on the remote control 900.

21 The During program menus (including Hidden menus and Program  
22 Overlay menus) are displayed by the set top terminal 220 only after the subscriber has  
23 selected a television program. In order to avoid disturbing the subscriber, the set top  
24 terminal 220 does not display the Hidden menus until the subscriber selects the  
25 appropriate option to display a Hidden menu. The Hidden menus contain options that are  
26 relevant to the program selected by the subscriber. For example, a Hidden may contain  
27 options that enable a subscriber to enter an interactive mode or escape from the selected  
28 program.

1 Program Overlay menus are similar to Hidden menus because they occur during  
2 a program and are related to the program being viewed. However, the Program Overlay  
3 menus are displayed concurrently with the program selected by the subscriber. Most  
4 Program Overlay menus are small enough on the screen to allow the subscriber to  
5 continue viewing the selected program comfortably.

6 As summarized above, images or programs may be selected for display by  
7 sequencing through a series of menus. Figure 17 is an example of one possible structure  
8 for a series of menus. Generally, the sequence of menus is structured with an  
9 Introductory menu, a Home menu, various major menus and a multitude of submenus.  
10 The submenus can include promotional menus and During Program menus. For example,  
11 at the Home menu portion of the sequence of menus and corresponding software routines,  
12 a subscriber may select one of the Major menus and start a sequence of menu displays.  
13 Alternatively, a subscriber may go directly to a major menu by depressing a menu select  
14 button on remote control 900.

15 At any time during the menu sequence, the subscriber may depress a Major menu  
16 button to move into another series of menus. In this way, a subscriber may move from  
17 Major menu to Major menu.

18 Shown in Figure 17 is a Major menu 1046 for the national broadcaster 110. The  
19 Major menu 1046, and the accompanying submenus, allow the national broadcaster's  
20 electronic program guide, such as the program guide 310 of Figure 15a, to be  
21 incorporated into the menu driven program access system. Alternately, the national  
22 broadcaster's electronic program guides could be provided as a stand-alone product.

23 The various software subroutines executed by the set top terminal 220 allow a  
24 subscriber to sequence the menus, navigating through the various menus of the present  
25 invention. A subscriber may sequence back through menus or return to the Home menu  
26 with a single touch of the Home menu button on remote 900.

27 An Introductory menu screen 1000 automatically appears upon power-up and  
28 initialization of the set top terminal 220. From this Introductory menu screen 1000, the  
29 set top terminal software will normally advance the subscriber to the Home menu screen

1 1010. The Home menu 1010 is the basic menu that the subscriber will return to in order  
2 to make the first level of viewing decisions. When the set top terminal software is  
3 displaying the Home menu 1010, the subscriber is able to access any television  
4 programming option. The software allows programming options to be entered through  
5 cursor movement on the screen and directly by button selection on the remote control  
6 900.

7 In the normal progression through the menu screens, the software will forward the  
8 subscriber to a Major menu screen 1020 in response to the subscriber's remote control  
9 900 selection or highlighted cursor selection from the Home menu screen 1010. The  
10 selections displayed on the Home menu 1010 are for large categories of programming  
11 options.

12 Following the Major menu 1020, the subscriber may navigate through one or  
13 more submenu screens 1050 from which the subscriber may choose one particular  
14 program for viewing. For most programming selections, the subscriber will proceed from  
15 the Home menu 1010 to a Major menu 1020 and then to one or more submenus 1050.  
16 However, for certain programming options or functions of the set top terminal 220, the  
17 subscriber may skip one or more menus in the sequence.

18 The During Program menus are submenus enabled by the set top terminal  
19 software only after the subscriber has selected a television program. These menus  
20 provide the subscriber with additional functionality and/or additional information while  
21 viewing a selected program. The During Program menu sequence can be further  
22 subdivided into at least two types of menus, Hidden menus 1380 and Program Overlay  
23 menus 1390.

24 To avoid disturbing a subscriber during viewing of a program, the Hidden menus  
25 1380 are not shown to the subscriber but instead "reside" at the set top terminal 220. The  
26 set top terminal 220 awaits a button entry either from the remote control 900 or the set  
27 top terminal 220 buttons before executing or displaying any Hidden menu 1380 options.  
28 The set top terminal software provides the subscriber with additional functions such as

1 entering an interactive mode or escaping from a selected program through use of Hidden  
2 menus 1380.

3 Program Overlay menus 1390 are similar to Hidden menus 1380. However, the  
4 Program Overlay menus 1390 are overlayed onto portions of the displayed video and not  
5 hidden. The software for the Program Overlay menus 1390 allows the subscriber to  
6 continue to watch the selected television program with audio but places graphical  
7 information on a portion of the television screen. Most Program Overlay menus 1390 are  
8 graphically generated to cover small portions of video. Some Program Overlay menus  
9 1390, which are by their nature more important than the program being viewed will  
10 overlay onto greater portions of the video. Examples of types of Program Overlay menus  
11 1390 include Notification menus 1392 and Confirmation menus 1394. In an  
12 embodiment, the software for the Program Overlay menus 1390 controls the reduction  
13 or scales down the (entire) programs video and redirects the video to a portion of the  
14 screen.

15 Submenus may provide the cost of viewing the program and the program's length  
16 in hours and minutes. From the submenus, the subscriber is given at least three options:  
17 (1) to purchase a program, (2) to return to the previous menu, and (3) to press "go" and  
18 return to regular TV. The subscriber may also be given other options such as previewing  
19 the program.

20 Using an on-screen menu approach to program selection, there is nearly an  
21 unlimited number of menus that can be shown to the subscriber. The memory capability  
22 of the set top terminal 220 and the quantity of information that is sent using the program  
23 control information signal are the only limits on the number of menus and amount of  
24 information that can be displayed to the subscriber. The approach of using a series of  
25 menus in a simple tree sequence is both easy for the subscriber to use and simply  
26 implemented by the set top terminal 220 and remote control device 900 with cursor  
27 movement. A user interface software programmer will find many obvious variations  
28 from the preferred embodiment described.

1           The set top terminal 220 may generate and create menus using, in part,  
2 information stored in its graphics memory. Referring to Figures 18a-18c, a background  
3 graphics file 800 will store menu backgrounds and a logo graphics file 820 will store any  
4 necessary logos. A menu display and cursor graphics file 850 will store menu display  
5 blocks and cursor highlight overlays as well as any other miscellaneous files needed to  
6 build the menus. Using this method of storing menus, the menus can be changed by  
7 reprogramming a graphics memory 620 of the set top terminal 220 through instructions  
8 from either the network controller 214 or operations center 202.

9           A microprocessor in the set top terminal 220 performs the steps required to create  
10 a menu using stored information. The microprocessor fetches a background file, logo  
11 file, menu display and cursor file in most instances. The microprocessor fetches text  
12 from long-term 875, intermediate-term 877, or short-term 879 storage depending on  
13 where the text is stored. Using a video combiner 886 (or like device), the stored  
14 information is combined with video and the entire image is sent to the television screen  
15 888 for display.

16           In an embodiment, a graphics controller is used to assist the set top terminal 220  
17 in generating menus. Menu generation by the set top terminal 220 begins with the  
18 building of a Major menu screen, which includes background graphics for that Major  
19 menu 1020. The background graphics may include an upper window across the top of  
20 the screen and a lower window across the bottom of the screen. The background graphics  
21 may be generated from the background graphics file 800 in the memory files of the  
22 graphics memory. In addition, logo graphics may be generated. Such graphics may  
23 include an icon window, a cable company logo, a channel company logo, and two "go"  
24 buttons.

25           The text for each Major menu 1020 may be generated separately by a text  
26 generator in the set top terminal 220. Those portions of the text that generally remain the  
27 same for a period of weeks or months may be stored in EEPROM or other local storage.  
28 Text that changes on a regular basis, such as the movie titles (or other program  
29 selections), is transmitted to the set top terminal 220 by either the operations center 202

1 or the network controller 214 of the cable headend 208. In this manner, the cable  
2 headend 208 may change the program selections available on any Major menu 1020 by  
3 modifying the program control information signal sent by the operations center 202 and  
4 transmitting any changes using a set top terminal control information signal (STTCIS).

5 Day, date and time information may be added to each Major menu 1020. This  
6 information is sent from the operations center 202, the cable headend 208 (signal  
7 processor 209 or network controller 214), the uplink site, or generated by the set top  
8 terminal 220 internally.

9 The creation and display of program description submenus is performed by the  
10 set top terminal 220 in a manner similar to that described above. Each submenu may be  
11 created in parts and combined before being sent to the television screen. Background  
12 graphics and upper and lower windows may be used. Likewise, a video window and half-  
13 strip window can be generated from information in storage on the EEPROM.

14 In addition to graphics and text, some submenus include windows that show  
15 video. Such video may be still or moving pictures. Still pictures may be stored in a  
16 compressed format (such as JPEG) at the set top terminal 220. Video stills may be  
17 transmitted by the operations center 202 through the program control information signal  
18 from time to time.

19 Moving video pictures may be obtained directly from a current video feed as  
20 described above. Depending on video window size, this may require manipulation of the  
21 video signal, including scaling down the size of the video and redirecting the video to the  
22 portion of the menu screen which is within the video window of the menu.  
23 Alternatively, the video may be obtained from a split screen channel. Such a method  
24 involves the use of split screen video techniques to send multiple video clips on a single  
25 channel at a given time. The set top terminal 220 would scale the picture, if necessary,  
26 and redirect it to the correct position on the screen using known scaling and positioning  
27 techniques. Additional circuitry may be required in the set top terminal 220 to perform  
28 adequate scaling and repositioning.

1 To avoid the need for redirecting video into the portion of the screen which  
2 houses the video window, masking and menu graphics may be used to cover the portions  
3 of the channel video that are not needed. This masking technique allows the split screen  
4 video to remain in the same portion of the screen that it is transmitted by the operations  
5 center 202. The masking is then adjusted to cover the undesired portions of the screen.  
6 These masks are stored in the background graphics file similarly to other background files  
7 for menus.

8 The split screen video technique may also be used for promoting television  
9 programming. Since a great number of short video clips may be sent continuously, full  
10 or partial screen promotionals (or informationals) may be provided to the subscriber.  
11 With this large quantity of promotional video, the subscriber is given the opportunity to  
12 "graze" through new movie or television programming selections. The subscriber simply  
13 grazes from promotional video to promotional video until the desired television program  
14 is discovered.

15 F. Detailed Set Top Terminal Description

16 The set top terminal 220 receives and manipulates signals from the cable headend  
17 208. The set top terminal 220 is equipped with local computer memory and the capability  
18 of interpreting the digitally compressed signal to produce menus for the subscriber. The  
19 remote control 900 communicates the subscriber's selections to the set top terminal 220.  
20 The subscriber's selections are generally based upon menus or other prompts displayed  
21 on the television screen.

22 Figure 19 shows the basic hardware components of the set top terminal 220. The  
23 set top terminal 220 has a tuner 603, digital demodulator 606, decryptor 600, and  
24 demultiplexers 609, 616 as well as audio equipment 612 and a remote control interface  
25 626 for receiving and processing signals from the remote control unit 900. A modem 627  
26 allows communication between a microprocessor 602 and the cable headend 208. An  
27 NTSC encoder 625 provides a standard NTSC video output.



1 The microprocessor 602 is capable of executing program instructions stored in  
2 memory. These instructions allow a subscriber to access various menus by making  
3 selections on the remote control 900.

4 The manner in which the video is decompressed and the menus are generated  
5 from the program control information signal or STTCIS varies depending on the specific  
6 embodiment of the invention. Video decompressors 618 and 622 may be used if the  
7 video is compressed. The program control information signal may be demultiplexed into  
8 its component parts, and a video decompressor 618, graphic decompressor, text generator  
9 and video combiner 624 may be used to assist in creating the menus.

10 In addition to the menu format information that is stored in graphics memory, the  
11 set top terminal 220 also stores data tracking those programs that have been selected for  
12 viewing. By gathering this data, the set top terminal 220 can maintain an accurate record  
13 of all programs accessed/watched by storing the data in EEPROM or RAM.  
14 Subsequently, this data can be transmitted to the cable headend 208, where it can be used  
15 in carrying out network control and monitoring functions. Such data transmissions  
16 between the set top terminal 220 and cable headend 208 can be accomplished, for  
17 example, through upstream transmission over the cable network or over telephone lines  
18 through the use of telephone modems. Where upstream transmission over the cable  
19 network is used, the set top terminals 220 can complete data transmissions on a scheduled  
20 (e.g., using a polling response or status report to respond to polling requests sent from the  
21 cable headend 208) or as-needed (e.g., using a random access technique) basis.

22 Figure 20a shows the front panel of the set top terminal 220, which includes an  
23 infrared sensor 630 and a series of LED displays 640. The LED displays 640 may  
24 indicate with an icon or a letter (e.g. A-K) the Major menu currently selected by the set  
25 top terminal 220 or the channels selected directly by a subscriber, or menu channel  
26 selections (e.g., from 1 to 50). Further displays may include current channel, time,  
27 volume level, sleep time, parental lock (security), account balance, use of a hardware  
28 upgrade, second channel being recorded by the VCR, use of the Level D music hardware  
29 upgrade in a separate room, a channel being viewed on another television that is coupled

1 to the set top terminal 220, and any other displays useful to a subscriber to indicate the  
2 current status of the set top terminal 220. The LEDs 640 may also provide an indication  
3 of the digital audio channel currently tuned.

4 The set top terminal 220 includes a flapped opening 635 on its front that allows  
5 the insertion of a magnetic cartridge (or similar portable storage device, including optical  
6 disk, ROM, EPROM, etc. not shown). This cartridge opening 635 allows the set top  
7 terminal 220 to be upgraded or reprogrammed locally with the use of a magnetic tape  
8 cartridge.

9 On the top or cover of the set top terminal 220 are located pushbutton controls  
10 645. Any function that can be performed on the remote 900 may also be performed at the  
11 set top terminal 220 using the duplicative pushbutton controls 645.

12 Figure 20b shows the back of the set top terminal 220, which includes a pair of  
13 output terminals 650, pair of input terminals 652, pair of stereo/audio output terminals  
14 654, satellite dish input port 656, telephone jack 658 and an RS-422 port 660. In  
15 addition, an upgrade port 662 and a cover plate 664 are held in place by a series of sheet  
16 metal screws. One of the output terminals 650 is for a television and the other is for a  
17 VCR or other video recording device. The set top terminal 220 is equipped to handle  
18 incoming signals on one or two cables using the input terminals 652. The phone jack 658  
19 and an RS-232 or RS-422 port 660 are provided for maintenance, trouble shooting,  
20 reprogramming and additional customer features, such as connection to a digital camera.  
21 In alternate embodiments, the telephone jack 658 may be used as the primary mode of  
22 communication between the cable headend 208 and the set top terminal 220. This  
23 connection is possible through the local telephone, cellular telephone or a personal  
24 communications network (PCN).

25 The basic programming of each set top terminal 220 is located on ROM within  
26 the set top terminal 220. Random access memory, the magnetic cartridge capability, and  
27 the expansion card slot 635 each allow upgrades and changes to be easily made to the set  
28 top terminal 220. The upgrade cards may be daisy-chained together to provide greater  
29 functionality for the set top terminal 220.

1 In an embodiment, the set top terminal 220 includes a hardware upgrade port 662,  
2 in addition to expansion card slots. The hardware upgrade port 662 accommodates a  
3 four-wire (or more) connection for: (1) error corrected, decrypted data output of the set  
4 top terminal 220, (2) a control interface, (3) decompressed video output, and (4) a video  
5 input port. In an embodiment, multiple wires are used to perform each of the four  
6 functions. The four sets of wires are combined in a single cable with a single multipin  
7 connector.

8 Multipin connections may be used for the multiwire cable. The multipin  
9 connection 662 may range from DB9 to DB25. A variety of small computer systems  
10 interface (SCSI) ports may also be provided. Alternatively, four or more ports may be  
11 provided instead of the single port depicted.

12 Another port 662 is used to attach the various hardware upgrades described below  
13 to a set top terminal 220. An embodiment has a number of hardware upgrades available  
14 for use with a set top terminal 220, including: (1) a Level A interactive unit, (2) a Level  
15 B interactive unit, (3) a Level C interactive unit with compact disc capability, (4) a Level  
16 D digital radio tuner for separate room use, and (5) a Level E information download unit.  
17 Each of these upgrades may be connected to the set top terminal 220 unit through the  
18 upgrade port 662 described earlier. The same four wires in a single cable described  
19 earlier may be used.

20 Existing set top converter boxes such as those made by Scientific Atlanta or  
21 General Instruments are presently unequipped to handle the menu selection system of the  
22 present invention. Thus, hardware modifications are necessary in order to use the menu  
23 selection system with existing set top converter technology.

24 An upgrade card addition to a set top converter is depicted in Figure 21. The card  
25 700 shown provides the additional functionality needed to utilize the menu system with  
26 existing set top converter technology. The primary functions the card 700 adds to the  
27 set top converter are the interpreting of program control information signals, generating  
28 of menus, sequencing of menus, and, ultimately, the ability of the subscriber to select a  
29 channel through the menu system without entering any channel identifying information.

1 The card 700 also provides a method for a remote location, such as the cable headend  
2 208, to receive information on programs watched and control the operation of the set top  
3 converter 220 and the card 700. The programs watched information and control  
4 commands may be passed from the cable headend 208 to the card 700 using telephone  
5 lines coaxial cable, fiber optic cable, wireless means and by satellite.

6 The primary components of the card 700 are a PC chip CPU 702, a VGA graphic  
7 controller 704, a video combiner 706, logic circuitry 708, NTSC encoder 710, a receiver  
8 712, demodulator 714, and a dialer 716. The card 700 operates by receiving the program  
9 control information signal from the cable headend 208 through the coaxial cable. The  
10 logic circuitry 708 of the card 700 receives data, infrared commands, and synchronization  
11 signals from the set top converter. Menu selections made by the subscriber on the remote  
12 control 900 are received by the set top converter's infrared equipment and passed through  
13 to the card 700. The card 700 interprets the infrared signal and determines the program  
14 (or menu) the subscriber has selected. The card 700 modifies the infrared command to  
15 send the program selection information to the set top converter 221. The modified  
16 infrared command contains the channel information needed by the set top converter 220.  
17 Using the phone line and dialer 716, the card 700 is able to transmit program access  
18 information to the cable headend 208.

19 G. Program Control Information Signal

20 Throughout this application, the term "program control information" is used to  
21 indicate control information coming from the cable headend 208 to the set top terminal  
22 220, whether it is sent directly from the operations center 202, processed by the network  
23 controller 214 and then forwarded to the set top terminal 220, or transmitted over  
24 telephone lines.

25 The program control information signal may reach the subscriber's home in a  
26 compressed format and be decompressed prior to viewing. Included in the delivered  
27 signal is information that enables equipment at the subscriber's home to display menus  
28 for choosing particular programs. The delivered program signal may also include the  
29 local authorization code, which allows for display of programs and channels of

1 programming. Depending on the particular embodiment, the television program signal  
2 may arrive at the subscriber's home through one or more connections such as coaxial  
3 cables, T1 and T3 lines, Integrated Services Digital Network (ISDN) lines and  
4 Asymmetric Digital Signal Lines (ADSL) cables, twisted pairs, cellular telephone  
5 connections, local area networks, direct satellite broadcasts, terrestrial broadcasts, or  
6 personal communications network (PCN) hookups.

7 The program control information signal is generated by the operations center 202  
8 and provides the network controller 214 with data on the scheduling and description of  
9 programs. In an alternate configuration, this data is sent directly to the set top terminal  
10 220 for display to the subscriber. In an embodiment, the program control information  
11 signal is stored and modified by the network controller 214 and sent to the set top  
12 terminal 220 in the form of the STTCIS. The set top terminal 220 integrates either the  
13 program control information signal or the STTCIS with data stored in the memory of the  
14 set top terminal 220 to generate on-screen menus that assist the subscriber in choosing  
15 programs for display.

16 The types of information that can be sent using the program control signal  
17 include: number of program categories, names of program categories, what channels are  
18 assigned to a specific category (such as specialty channels), names of channels, names  
19 of programs on each channel, program start times, length of programs, description of  
20 programs, menu assignment for each program, pricing, whether there is a sample video  
21 clip for advertisement for the program, and any other program, menu or product  
22 information. As noted above, the program control signal may also include local  
23 authorization codes.

24 With a minimal amount of information being communicated to the set top  
25 terminal 220 on a regular basis, the set top terminal 220 is able to determine the proper  
26 menu location for each program and the proper time and channel to activate for the  
27 subscriber after a menu selection. The program control information signal and STTCIS  
28 can be formatted in a variety of ways and the on-screen menus can be produced using  
29 many different methods. For instance, if the program control information signal carries

1 no menu format information, the menu format for creating the menus can be fixed in  
2 ROM at the set top terminal 220. In an embodiment, the menu format information is  
3 stored at the set top terminal 220 in a temporary memory device such as a RAM or  
4 EPROM. New menu format information is sent via the program control information  
5 signal or the STTCIS to the set top terminals 200 whenever a change to a menu format  
6 is desired.

7 In an embodiment, the menu formats remain fixed and only the text changes. In  
8 this way the program control information signal can be limited to primarily text and a text  
9 generator can be employed in the set top terminal 220. Another simple embodiment uses  
10 a separate channel full-time (large bandwidth) just for the menu information.

11 Live video signals may be used in windows of certain menus. These video signals  
12 can be transmitted using the program control information signal or STTCIS, or can be  
13 taken off channels being transmitted simultaneously with the menu display. Video for  
14 menus, promos or demos may be sent to the set top terminal 220 in several formats,  
15 including (1) on a dedicated channel, (2) on a regular program channel and scaled to size,  
16 or (3) along with the program control information signal. For example, a large number  
17 of short promos or demo video may be sent using a split screen technique on a dedicated  
18 channel. A multiple window technique may be used with the menus to display a  
19 description of a program and one or more video frames that assist the subscriber in  
20 selecting the program.

21 The program control information signal generated by the operations center 202  
22 provides data on the scheduling and description of programs to the network controller  
23 214 or, in an alternate configuration, directly to the set top terminal 220 for display to the  
24 subscriber. In an embodiment, the program control information signal is stored and  
25 modified by the network controller 214 and sent to the set top terminal 220 in the form  
26 of the STTCIS. This configuration is required to accommodate differences in individual  
27 cable systems and possible differences in set top terminal devices. The set top terminal  
28 220 integrates either the program control information signal or the set top terminal

1 control information stream together with data stored in the memory of the set top terminal  
2 220, to generate on-screen displays for assisting the subscriber in choosing programs.

3 The goal of the menu driven program selection system is to allow the subscriber  
4 to choose a program by touring through a series of menus, organized generally as  
5 depicted in Figure 17, utilizing the remote control 900 for cursor movement. The final  
6 choice in the series of menus will identify one particular channel and one time for  
7 activation of that channel. Armed with a channel and activation time the set top terminal  
8 220 can display the selected program on the television for the subscriber. To achieve this  
9 goal an intelligent alpha-numeric code is assigned to each program. This alpha-numeric  
10 code identifies the category of the program, the menu in which the program should be  
11 displayed, its transmission time(s), and the position on the menu that the program should  
12 be displayed.

13 The program control information, including menu codes, may be sent  
14 continuously from the operations center 202 to the network controller 214, and ultimately  
15 to the set top terminal 220.

16 Table A shows the basic programming information that may be sent to the set top  
17 terminal 220. The program descriptions shown are coded abbreviations. For example,  
18 C for comedy, N for news, S for sports, A for cartoons, and Tx for text. If there is a  
19 textual description for a program, such as a movie, the description may be given  
20 following that program's coded description or may be communicated following the four  
21 hours' worth of programming information. As is shown in the coded listing, program  
22 descriptions for programs greater than a half hour in length need not be repeated (each  
23 half hour). The video description code informs the set top terminal 220 of whether there  
24 is still or live video available to advertise the program.

25 For example, a sporting program may be assigned a code of B35-010194-1600-  
26 3.25-Michigan St. vs. USC. The letter B would assign the program to category B, sports.  
27 The second alpha-numeric character number 3 would assign the program to the third  
28 menu of the sports category. The third character of the code, number 5, assigns the  
29 program to the fifth program slot on the third menu. The next six characters, 01/01/94,

represent the date. The following four characters, 1600 represent the start time which is followed by the length of the program and the program name. This entry represents a sports show, a college football game, which will be aired at 4:00PM on New Years day 1994.

**TABLE A**

**12:00 PM**

*Ch.	*Program name	*Program length	*Menu code	*Description	*Video
1	Cheers	.5	E24	C	N
2	Terminator	2.0	A33	Tx	S
3	PrimeTime	1.0	D14	N	N
4	Football Special	.5	B24	S	N

**12:30 PM**

*Ch.	*Program name	*Program length	*Menu code	*Description	*Video
1	Simpsons	.5	E14&C13	C	S
4	Football Game	3.0	B13	S	N
.					
.					

In the 12:30 Channel 1 entry of Table A, two menu codes are shown. By allowing two menu codes, programs that may fit under two different category descriptions may be shown in both menus to the subscriber. With this minimal amount of information being communicated to the set top terminal 220 on a regular basis, the terminal is able to determine the proper menu location for each program and the proper time and channel to activate for the subscriber after his menu selection.

In the 12:30 Channel 1 entry of Table A, two menu codes are shown. By allowing two menu codes, programs that may fit under two different category descriptions may be shown in both menus to the subscriber. With this minimal amount of information being



communicated to the set top terminal 220 on a regular basis, the terminal is able to determine the proper menu location for each program and the proper time and channel to activate for the subscriber after his menu selection.

Table B shows an example Events Table that may be downloaded to a set top terminal 220 using the Event.Dat file which contains information about events and

**TABLE B**

Field #	Field Type	
1	Event Type 1 = YCTV 2 = Pay-Per-View 3 = Reg. TV	Unsigned Int
2	Event ID	Unsigned Int
3	Global Channel ID	Unsigned Int
4	Price (in Cents)	Unsigned Int
5	Start Time	HH:MM:SS
6	End Time	HH:MM:SS
7	Start Date	MM/DD/YY
8	End Date	MM/DD/YY
9	P-Icon	ASCIIZ
10	Name	ASCIIZ
11	Description	ASCIIZ

pricing. As shown in the table, the three columns of the Events Table identify the field number, the field itself and the type of information downloaded in the Event.Dat file. The first column contains the field numbers 1 through 11. The middle column contains the corresponding field parameters, including the event type, event ID, global channel ID, price, start time, end time, start date, end date, P- icon, name and description. The third column contains corresponding field type information. Field type information typically consists of an unsigned integer; hours, minutes and seconds; months, day and year; and ASCII character identifier.

Table C shows an example Event.Dat data file. In particular, Table C shows two data streams corresponding to two event types. The first data stream identifies a YCTV™ event in the first field. The second field designates the event ID, which is 1234 in this example. The third field includes the global channel ID number two. The fourth

field indicates the cost of 50 cents for this event. The fifth and sixth fields indicate the respective start and end times of 3:00 AM to 3:00 PM, respectively. The seventh and eighth fields show the corresponding start and end dates, designated as 8/25/93 and 8/27/93, respectively. Field nine indicates the P-icon set to PBS.PCX graphics file. Finally, fields ten and eleven indicate the name and description of the events selected, which in this case are Sesame Street<sup>TM</sup> and Barney<sup>TM</sup>. The second data stream in the Event.Dat example shown in Table C includes analogous information for Terminator IV<sup>TM</sup>, which is designated in field one as a pay-per-view event.

TABLE C

**Event.Dat Example**

1`1234`2`50`03:00:00`15:00:00`08/25/93`08/27/93`pbs.pcx`Sesame Street & Barney's Sesame Street and Barney Abstract
2`1234`2`50`20:00:00`22:00:00`08/25/93`08/25/93`t4.pcx`Terminator 4`Terminator 4 Abstract

The program control information signal and STTCIS can be formatted in a variety of ways and the on-screen menus can be produced in many different ways. For instance, if the program control information signal carries no menu format information, the menu format for creating the menus can be fixed in ROM at the set top terminal 220. This method allows the program control information signal to carry less information but has the least flexibility since the menu formats can not be changed without physically swapping the ROM.

In an embodiment, the menu format information is stored at the set top terminal 220 in temporary memory either in a RAM, FLASH ROM, EEPROM or EPROM. This configuration provides the desired flexibility in the menu format while still limiting the amount of information needed to be communicated via the program control information signal. New menu format information can be sent via the program control information signal or the STTCIS to the set top terminals 220 each time there is a change to a menu.

Program access information for each program watched is stored at the set top terminal 220 until it is polled by the network controller 214 for information retrieval using the program control information signal or STTCIS. This information retrieval can

1 be accomplished by using the polling request message and response formats, 920 and  
2 920' respectively, as shown, and Figures 22a and 22b, and described below, but any  
3 suitable polling request and response message format may be used to interrogate each set  
4 top terminal 220 sequentially, one by one. The set top terminals 220 are identified by a  
5 unique address and set top terminal identifier. The set top terminal 220 may transmit  
6 information and messages to the network controller 214 only when given permission by  
7 the network controller 214 to do so.

8 Where, for example, specialty programs have been accessed since the previous  
9 poll, the set top terminal 220 is given permission to transmit a polling response 920' in  
10 the form of a status report that includes any such access information. The network  
11 controller's control receiver (not shown) is tasked with the receipt of set top terminal  
12 polling responses or status reports. These status reports generally include information  
13 that allows the network controller 214 to track a subscriber's program access history.

14 Figure 22a shows an embodiment of a frame format message 920 used for polling  
15 the set top terminals 220. This frame format 920 consists of six fields, namely: (1) a  
16 leading flag 922 at the beginning of the message, (2) an address field 924, (3) a subscriber  
17 region designation 926, (4) a set top terminal identifier 928 that includes a polling  
18 command/response (or P/F) bit 930, (5) an information field 932, and (6) a trailing flag  
19 934 at the end of the message.

20 The eight-bit flag sequence 922 that appears at the beginning and end of a frame  
21 is used to establish and maintain synchronization. Such a sequence typically consists of  
22 a "01111110" bit-stream. The address field 924 designates a 4-bit address for a given set  
23 top terminal 220. The subscriber region designation 926 is a 4-bit field that indicates the  
24 geographical region in which the subscriber's set top terminal 220 is housed. The set top  
25 terminal identifier 928 is a 16-bit field that uniquely identifies each set top terminal 220  
26 with a 15-bit designation followed by an appended P/F bit 930. Although field size is  
27 provided by this example, a variety of sizes can be used with the invention.

28 The P/F bit 930 is used to command a polling response from the set top terminal  
29 220 addressed, as described below. The response frame format 920' also provides a

1 variable-length information field 932' for other data transmissions, such as information  
2 on system updates. The frame format 920' ends with an 8-bit flag (or trailing flag) 934'  
3 that is identical in format to the leading flag 922', as set forth above. Other frame  
4 formats (e.g., MPEG) will be apparent to one skilled in the art and can be easily adapted  
5 for use with the system.

6 Figure 22b shows an example of frame format 920' for the status reports received  
7 from the set top terminals 220 during the polling cycle. This frame format is identical to  
8 the polling request message format 920 and, as described, includes: (1) a leading flag  
9 922' at the beginning of the message, (2) an address field 924', (3) a subscriber region  
10 designation 926', (4) a set top terminal identifier 928' that includes a polling  
11 command/response (or P/F) bit 930', (5) an information field 932', and (6) a trailing flag  
12 934' at the end of the message.

13 The information field 932' remains variable in length so that the status of an  
14 indeterminate number of programs, represented at 931, accessed can be included in the  
15 frame. In this way, the control message length of the polling request message is minimal  
16 since the network controller 214 does not transmit such access information. After a  
17 polling response by a given set top terminal 220, however, the control message length  
18 increases in proportion to the number of programs accessed.

19 During transmission, the P/F bit is used to carry out the polling function. In  
20 particular, the P/F bit is set to a "1" position to command a polling response from the set  
21 top terminal 220 whose address is identified in the frame. The set top terminal 220  
22 addressed must respond to the command in the same P/F bit also set to the "1" position.  
23 The response will include the number of programs accessed and their corresponding  
24 event identification numbers as shown in Figure 22b at 931. In cases where the set top  
25 terminal 220 has not accessed any programs since the previous polling cycle, the set top  
26 terminal 220 responds with the P/F bit set to "1" and the programs access block denoting  
27 zero programs accessed.

28 Through the polling cycle, the network controller 214 acquires the information  
29 needed to operate the system 200. During the polling cycle, the network controller 214

1 sends signals to the set top terminals 220 to authorize both their operation and access to  
2 specific channels. If, for example, a subscriber has failed to pay a recent bill, the network  
3 controller 214 can deauthorize the subscriber's set top terminal 220. Likewise, when the  
4 subscriber orders a program or channel, the network controller 214 checks the  
5 subscriber's account for good standing by reading the proper database file. After the  
6 check, the network controller 214 then either authorizes or deauthorizes access by the set  
7 top terminal 220. The authorization and deauthorization may be provided by any of the  
8 methods described with respect to Figures 10 - 12, for example. As a result, the cycle  
9 requires a series of requests and responses to operate.

10 A second method for the network controller 214 to receive information from the  
11 set top terminals 220 is through the use of a random access scheme. In this method,  
12 individual set top terminals 220 can send control-related messages to the network  
13 controller 214 without being polled. This scheme is particularly useful in networks where  
14 subscriber regions include potentially large numbers of subscribers. High concentrations  
15 of subscribers may be found, for example, in large metropolitan areas. In such cases, the  
16 polling cycle can be replaced with a more sophisticated random access strategy such as  
17 carrier-sense multiple access with collision detection (CSMA/CD). In this scheme, each  
18 set top terminal 220 must "listen" before it transmits and then does so only if it senses an  
19 idle medium. When the return link to the network controller 214 is silent, a given set top  
20 terminal 220 can transmit its messages. Any messages sent from a set top terminal 220  
21 to the network controller 214 would set the P/F bit 930' to a "0" position to indicate that  
22 the message is not in response to any command or polling request. In addition to  
23 CSMA/CD, other random access schemes can be used with the system, such as CDSL.

24 Yet another method for the network controller 214 to receive information from  
25 the set top terminals 220 is through the use of modems. In this arrangement, the set top  
26 terminals 220 communicate program access information and orders to the network  
27 controller 214 using telephone modems. The set top terminals 220 are equipped with a  
28 modem port to facilitate such operation. Thus, communications between a given set top  
29 terminal 220 and the network controller 214 can be established over telephone lines or

1 other media when cable traffic or other primary traffic is congested. A method includes  
2 using modems is in combination with a control or "hit" signal from the network controller  
3 214. A group (or region) of set top terminals 220 is "hit" simultaneously by the network  
4 controller 214 via the cable. Only those set top terminals 220 within the group that have  
5 data for the network controller 214 call the network controller 214 by modem. The  
6 network controller 214 is equipped with a bank of modems (organized to roll-over  
7 telephone calls) to answer the incoming calls.

8 Among the methods discussed for the network controller 214 to receive  
9 information from the set top terminals 220, polling allows the network controller 214 to  
10 conduct and control communications with set-top terminals 220 over the cable network  
11 in an orderly fashion. In particular, the network controller 214 can schedule data retrieval  
12 by polling the set top terminals 220 one by one. A random access method, on the other  
13 hand, does not allow the network controller 214 to maintain such orderly  
14 communications. Instead, the network controller 214 receives data from the set top  
15 terminals 220 at random, depending on when the cable medium is idle. This random  
16 reception of data lessens the degree of control that the network controller 214 has over  
17 set top terminal transmissions.

18 In between polling cycles, the program control information continues to supply  
19 the set top terminals 220 with menu information. In the simplest embodiment, the menus  
20 remain fixed and only the text changes. Thus, the program control information signal can  
21 be limited to primarily text and a text generator can be employed in the set top terminal  
22 220. This simple embodiment keeps the cost of the set top terminal 220 low and limits  
23 the bandwidth necessary for the program control information. Another simple  
24 embodiment uses a separate channel full-time (large bandwidth) just for the menu  
25 information. This separate channel would facilitate the rapid downloading of new  
26 graphics for the system and would enhance response time when text and other data  
27 information needs to be changed.

28 In an embodiment, the basic building blocks or templates of the on-screen menu  
29 displays will be stored in graphics memory consisting of nonvolatile RAM, FLASH

1 ROM, EPROM, or preferably, EEPROM, as shown as 620 in Figure 18a. Referring to  
2 Figure 19, with the information from the graphics memory 620, the microprocessor 602,  
3 graphics decompressor 622, a text generator (not shown in Figure 19, but incorporated  
4 if necessary), and video combiner 624 will build a menu screen.

5 The memory files of the graphics memory are preferably categorized into three  
6 categories, background graphics 800, logo graphics 820, and menu and display graphics  
7 850, as shown in Figure 18a.

8 The background graphics file 800 will store menu backgrounds such as: universal  
9 main menu backgrounds 804, universal submenu backgrounds 808, promo backgrounds  
10 812 and custom menu formats 816. The logo graphics file 820 will store any necessary  
11 logos such as: Your Choice TV™ logos 824, Network logo files 828, cable system logo  
12 files 832, studio logo files 836, and graphic elements file 840. The menu display and  
13 cursor graphics file 850 will store menu display blocks 854 and cursor highlight overlays  
14 858, as well as any other miscellaneous files needed to build the menus.

15 Using this method of storing menus discussed above, the menus can be changed  
16 by reprogramming the graphics memory 620 of the set top terminal 220. To revise the  
17 entire design of displayed menus, the network controller 214 or operations center 202  
18 instructs the EEPROM 620 to be erased and reprogrammed with new menu templates.  
19 To change one menu format or logo, the network controller 214 or operations center 202  
20 instructs just the one location in memory to be erased and rewritten. The menu  
21 reprogramming can also be done locally (at the set top terminal 220) by a serviceman.

22 As shown in Figure 18a, each memory subfile is further divided into various  
23 memory blocks. For example, the background graphics file 800 contains the universal  
24 main menu backgrounds 804. The universal main menu backgrounds memory 804  
25 includes memory units UM1 860, UM2 862 and UM3 863. Similarly, the logo graphics  
26 file 820 and menu display and cursor graphics file 850 contain individual subfile memory  
27 blocks (for example, studio logo file 836 has memory block SL1 864; menu display  
28 blocks 854 has memory menu display block MD1 866).

1           Figure 18b shows the hierarchical storage of text transmitted from the cable  
2 headend 208. Although text may be continuously transmitted with the video signals to  
3 set top terminals 220, text may also be transmitted intermittently. In such a case, the text  
4 is stored in the set top terminal 220. The text may be transmitted and stored in a  
5 compressed format using known techniques. Additionally, the text may be stored in the  
6 graphics memory 620 within the set top terminal 220.

7           Depending upon the use of the text, it will be stored in one of three portions of  
8 memory. Information sent with the text will either direct the text to a particular portion  
9 of memory, or include information as to the priority of text. The microprocessor 602,  
10 part of the set top terminal hardware represented at block 880, may then direct the text  
11 to the appropriate memory location for storage.

12           If the text is to be used frequently and over a long period of time a long term  
13 storage 875 will be used. If the text will be used for a shorter period of time (for  
14 example, a month), the text will be directed to an intermediate storage area 877. If the  
15 text is to be used almost immediately, or for a short period of time (for example, within  
16 a few days) the text is directed to a short term storage area 879. The microprocessor 602  
17 locates the appropriate text required for a particular menu and retrieves it from the  
18 appropriate portion of memory 620. The text is output from the graphics memory 620  
19 to the text generator 621. Text generated from the text generator 621 is thereafter  
20 directed to text/graphics video combiner 624.

21           Figure 18c shows the steps performed by the microprocessor 602 for creating a  
22 menu based upon a series of overlay screens. These instructions are stored in memory  
23 within the set top terminal 220 in a screen data file. The screens data file instructs the  
24 microprocessor 602 on the location of each graphics file on the screen. An example  
25 screen data file is shown in Table D, wherein the screen data file specifies menu data  
26 positioning in terms of, for example, x- and y-pixel positions, height and width, color  
27 codes and fonts. Alternatively, instructions or routines may be transmitted from the  
28 operations center 202 to be stored in memory within the individual set top terminals 220.



TABLE D

~ The following data lines are for the main menu												
~												
		Screen Type			Template File			Description				
SCREEN		`@MAIN			`main menu.pcx			`Main Menu				
~												
		Justify	X	Y	Ht	Wd	FColor	BColor	Font			
STR POS	`Left	`165	`85	`30	`300	`27	`55	FUTUR14.GFT				
STRING `MAIN MENU												
~												
		Justify	X	Y	Hght	Wdt						
PCX POS	`LEFT	`190	`75	`200	`200							
PCX example.pcs												
~												
		Justify	X	Y	Ht	Wd	FColor	BColor	Font	X	Y	Ht
											Wd	
ITEM POS	`Left	`120	`100	`20	`400	`15	`25	FUTUR12.GFT		`1	1	0
											`420	
ITEM `@YCTV`YOUR CHOICE TV												
~												
		Justify	X	Y	Ht	Wd	FColor	BColor	Font	X	Y	Ht
											Wd	
ITEM POS	`Left	`120	`200	`20	`400	`15	`25	FUTUR12.GFT		`1	1	0
											`420	
ITEM `@PPV`PAY-PER-VIEW HIT MOVIES												

As shown at block 878 in Figure 18c, initially the microprocessor 602 instructs the tuner 603 to select a channel. The channel is decompressed, error corrected and decrypted, if necessary. If the video is to be reduced in size, so as to be placed within a video window, or is a split screen video window which must be enlarged, the video is scaled to the appropriate size. Additionally, the video may be required to be redirected to a portion of the television screen, accomplished by creating a series of offsets for each pixel location of the video.

Graphics may also be used to create a menu in most instances. As shown in block 882, the microprocessor 602 may fetch a background file, a logo file, and a menu display and cursor file in most instances. Each of these files is decompressed 883, and then combined, block 886.

1                Similarly, the microprocessor 602 may fetch text, as shown in block 884.  
2                Depending upon the memory location of the text, the microprocessor 602 will fetch the  
3                text from long-term, intermediate-term, or short-term storage, as described above. Based  
4                upon this memory retrieval, the text is generated, block 885, and combined with the  
5                video (if any), with as many screens of a decompressed graphics as are necessary, and  
6                any text, block 886. The image or portions of the image are stored in the video combiner  
7                (for example, combiner 624 of Figure 19) until all overlays are received. Thereafter, the  
8                entire image is sent, under direction of another routine, to be displayed on the television  
9                screen, as represented by display block 888.

10              The terms and descriptions used herein are set forth by way of illustration  
11              only and are not meant as limitations. Those skilled in the art will recognize that  
12              numerous variations are possible within the spirit and scope of the invention as defined  
13              in the following claims.